# Safety Data Sheet according to (EC) No 1907/2006 as amended



SDS No. : 168433
V008.0

LOCTITE 542

Revision: 23.07.2025
printing date: 10.08.2025
Replaces version from: 05.12.2024

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

**1.1. Product identifier**
LOCTITE 542
UFI: 9KW2-R0SH-700N-JHS5

**1.2. Relevant identified uses of the substance or mixture and uses advised against**
Intended use:
Threadlocker

**1.3. Details of the supplier of the safety data sheet**
Henkel Ltd
Adhesives
Wood Lane End
HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (1442) 278000

SDSinfo.Adhesive@henkel.com
For Safety Data Sheet updates please visit our website www.mysds.henkel.com or www.henkel-adhesives.com.

**1.4. Emergency telephone number**
24 Hours Emergency Tel: +44 (0)1442 278497

## SECTION 2: Hazards identification

**2.1. Classification of the substance or mixture**

**Classification (CLP):**

| | |
|---|---|
| Serious eye irritation | Category 2 |
| H319 Causes serious eye irritation. | |
| Specific target organ toxicity - single exposure | Category 3 |
| H335 May cause respiratory irritation. | |
| Target organ: respiratory tract irritation | |
| Chronic hazards to the aquatic environment | Category 3 |
| H412 Harmful to aquatic life with long lasting effects. | |

**2.2. Label elements**

**Label elements (CLP):**

**Hazard pictogram:**



**Contains** Cumene hydroperoxide

| | |
|---|---|
| **Signal word:** | Warning |
| **Hazard statement:** | H319 Causes serious eye irritation.<br>H335 May cause respiratory irritation.<br>H412 Harmful to aquatic life with long lasting effects. |
| **Supplemental information** | Contains: methyl methacrylate May produce an allergic reaction. |
| **Precautionary statement:** | "***" ***For consumer use only: P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P501 Dispose of contents/container in accordance with national regulation.*** |
| **Precautionary statement: Prevention** | P261 Avoid breathing vapors.<br>P273 Avoid release to the environment. |
| **Precautionary statement: Response** | P337+P313 If eye irritation persists: Get medical advice/attention. |

**2.3. Other hazards**

None if used properly.

**Following substances are present in a concentration ≥ the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):**

This mixture does not contain any substances in a concentration ≥ the concentration limit for depiction in Section 3 that are assessed to be a PBT, vPvB or ED.

## SECTION 3: Composition/information on ingredients

**3.2. Mixtures**

**Declaration of the ingredients according to CLP (EC) No 1272/2008:**

| Hazardous components<br>CAS-No.<br>EC Number<br>REACH-Reg. No. | Concentration | Classification | Specific Conc. Limits, M-factors and ATEs | Add. Information |
|---|---|---|---|---|
| Cumene hydroperoxide<br>80-15-9<br>201-254-7<br>01-2119475796-19 | 1- < 3 % | STOT RE 2, H373<br>Skin Corr. 1B, H314<br>Acute Tox. 2, Inhalation, H330<br>Aquatic Chronic 2, H411<br>Acute Tox. 4, Oral, H302<br>Acute Tox. 4, Dermal, H312<br>Org. Perox. E, H242<br>STOT SE 3, H335 | Eye Irrit. 2; H319; C 1 - < 3 %<br>Skin Irrit. 2; H315; C 3 - < 10 %<br>Eye Dam. 1; H318; C 3 - < 10 %<br>STOT SE 3; H335; C >= 1 %<br>Skin Corr. 1B; H314; C >= 10 %<br>=====<br>dermal:ATE = 1.100 mg/kg | |
| N,N-Diethyl-p-toluidine<br>613-48-9<br>210-345-0 | 0,1- < 1 % | Acute Tox. 3, Oral, H301<br>Acute Tox. 3, Dermal, H311<br>Acute Tox. 3, Inhalation, H331<br>STOT RE 2, H373<br>Aquatic Chronic 3, H412<br>Skin Irrit. 2, H315 | dermal:ATE = 300 mg/kg<br>oral:ATE = 100 mg/kg<br>inhalation:ATE = 3 mg/l;vapour | |
| N,N-dimethyl-o-toluidine<br>609-72-3<br>210-199-8 | 0,1- < 1 % | STOT RE 2, H373<br>Acute Tox. 3, Oral, H301<br>Acute Tox. 3, Dermal, H311<br>Acute Tox. 3, Inhalation, H331<br>Aquatic Chronic 3, H412 | dermal:ATE = 300 mg/kg<br>oral:ATE = 100 mg/kg<br>inhalation:ATE = 0,5 mg/l;dust/mist | |
| methacrylic acid<br>79-41-4<br>201-204-4<br>01-2119463884-26 | 0,1- < 1 % | Acute Tox. 4, Oral, H302<br>Acute Tox. 3, Dermal, H311<br>Acute Tox. 4, Inhalation, H332<br>Skin Corr. 1A, H314<br>Eye Dam. 1, H318<br>STOT SE 3, H335 | STOT SE 3; H335; C >= 1 %<br>=====<br>dermal:ATE = 500 mg/kg<br>inhalation:ATE = 3,19 mg/l;dust/mist | |
| 1,4-Naphthalenedione<br>130-15-4<br>204-977-6 | 0,01- < 0,1 % | Acute Tox. 3, Oral, H301<br>Skin Corr. 1C, H314<br>Skin Sens. 1, H317<br>Eye Dam. 1, H318<br>Acute Tox. 1, Inhalation, H330<br>STOT SE 3, H335<br>Aquatic Acute 1, H400<br>Aquatic Chronic 1, H410 | M acute = 10<br>M chronic = 1 | |

**If no ATE values are displayed, please refer to LD/LC50 values in Section 11.**
**For full text of the H - statements and other abbreviations see section 16 "Other information".**

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

Inhalation:
Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:
Rinse with running water and soap.
Obtain medical attention if irritation persists.

Eye contact:
Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:
Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

**4.2. Most important symptoms and effects, both acute and delayed**
RESPIRATORY: Irritation, coughing, shortness of breath, chest tightness.

EYE: Irritation, conjunctivitis.

Prolonged or repeated contact may cause skin irritation.

**4.3. Indication of any immediate medical attention and special treatment needed**
See section: Description of first aid measures

## SECTION 5: Firefighting measures

**5.1. Extinguishing media**
**Suitable extinguishing media:**
water, carbon dioxide, foam, powder

**Extinguishing media which must not be used for safety reasons:**
High pressure waterjet

**5.2. Special hazards arising from the substance or mixture**
In the event of a fire, carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx) can be released.

**5.3. Advice for firefighters**
Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

**Additional information:**
In case of fire, keep containers cool with water spray.

## SECTION 6: Accidental release measures

**6.1. Personal precautions, protective equipment and emergency procedures**
Avoid contact with skin and eyes.
Wear protective equipment.
Ensure adequate ventilation.
Keep away from sources of ignition.

**6.2. Environmental precautions**
Do not empty into drains / surface water / ground water.

**6.3. Methods and material for containment and cleaning up**
Dispose of contaminated material as waste according to Section 13.
For small spills wipe up with paper towel and place in container for disposal.
For large spills absorb onto inert absorbent material and place in sealed container for disposal.

**6.4. Reference to other sections**
See advice in section 8

## SECTION 7: Handling and storage

**7.1. Precautions for safe handling**
Avoid skin and eye contact.
See advice in section 8

Hygiene measures:
Wash hands before work breaks and after finishing work.
Do not eat, drink or smoke while working.
Good industrial hygiene practices should be observed.

**7.2. Conditions for safe storage, including any incompatibilities**
Ensure good ventilation/extraction.
Refer to Technical Data Sheet.

**7.3. Specific end use(s)**
Threadlocker

## SECTION 8: Exposure controls/personal protection

**8.1. Control parameters**

**Occupational Exposure Limits**

Valid for
Great Britain

| Ingredient [Regulated substance] | ppm | mg/m$^3$ | Value type | Short term exposure limit category / Remarks | Regulatory list |
|---|---|---|---|---|---|
| Methacrylic acid<br>79-41-4<br>[METHACRYLIC ACID] | 20 | 72 | Time Weighted Average (TWA): | | EH40 WEL |
| Methacrylic acid<br>79-41-4<br>[METHACRYLIC ACID] | 40 | 143 | Short Term Exposure Limit (STEL): | 15 minutes | EH40 WEL |

**Occupational Exposure Limits**

Valid for
Ireland

| Ingredient [Regulated substance] | ppm | mg/m$^3$ | Value type | Short term exposure limit category / Remarks | Regulatory list |
|---|---|---|---|---|---|
| Methacrylic acid<br>79-41-4<br>[METHACRYLIC ACID] | 20 | 70 | Time Weighted Average (TWA): | | IR_OEL |
| Methacrylic acid<br>79-41-4<br>[METHACRYLIC ACID] | 40 | 140 | Short Term Exposure Limit (STEL): | 15 minutes | IR_OEL |

**Predicted No-Effect Concentration (PNEC):**

| Name on list | Environmental Compartment | Exposure period | Value | | | | Remarks |
|---|---|---|---|---|---|---|---|
| | | | mg/l | ppm | mg/kg | others | |
| .alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9 | aqua (freshwater) | | 0,0031 mg/l | | | | |
| .alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9 | aqua (intermittent releases) | | 0,031 mg/l | | | | |
| .alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9 | aqua (marine water) | | 0,00031 mg/l | | | | |
| .alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9 | sewage treatment plant (STP) | | 0,35 mg/l | | | | |
| .alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9 | sediment (freshwater) | | | | 0,023 mg/kg | | |
| .alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9 | sediment (marine water) | | | | 0,0023 mg/kg | | |
| .alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9 | Soil | | | | 0,0029 mg/kg | | |
| methacrylic acid 79-41-4 | aqua (freshwater) | | 0,82 mg/l | | | | |
| methacrylic acid 79-41-4 | Freshwater - intermittent | | 0,45 mg/l | | | | |
| methacrylic acid 79-41-4 | aqua (marine water) | | 0,082 mg/l | | | | |
| methacrylic acid 79-41-4 | sewage treatment plant (STP) | | 100 mg/l | | | | |
| methacrylic acid 79-41-4 | sediment (freshwater) | | | | 3,09 mg/kg | | |
| methacrylic acid 79-41-4 | sediment (marine water) | | | | 0,309 mg/kg | | |
| methacrylic acid 79-41-4 | Soil | | | | 0,137 mg/kg | | |
| methacrylic acid 79-41-4 | Predator | | | | | | no potential for bioaccumulation |

**Derived No-Effect Level (DNEL):**

| Name on list | Application Area | Route of Exposure | Health Effect | Exposure Time | Value | Remarks |
|---|---|---|---|---|---|---|
| .alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9 | Workers | inhalation | Long term exposure - systemic effects | | 6 mg/m3 | |
| methacrylic acid 79-41-4 | Workers | Inhalation | Long term exposure - local effects | | 88 mg/m3 | no potential for bioaccumulation |
| methacrylic acid 79-41-4 | Workers | Inhalation | Long term exposure - systemic effects | | 29,6 mg/m3 | no potential for bioaccumulation |
| methacrylic acid 79-41-4 | Workers | dermal | Long term exposure - systemic effects | | 4,25 mg/kg | no potential for bioaccumulation |
| methacrylic acid 79-41-4 | General population | Inhalation | Long term exposure - local effects | | 6,55 mg/m3 | no potential for bioaccumulation |
| methacrylic acid 79-41-4 | General population | Inhalation | Long term exposure - systemic effects | | 6,3 mg/m3 | no potential for bioaccumulation |
| methacrylic acid 79-41-4 | General population | dermal | Long term exposure - systemic effects | | 2,55 mg/kg | no potential for bioaccumulation |

**Biological Exposure Indices:**
None

**8.2. Exposure controls:**

Engineering controls:
Ensure good ventilation/extraction.

Respiratory protection:
Ensure adequate ventilation.
An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area
Filter type: A (EN 14387)

Hand protection:
Chemical-resistant protective gloves (EN 374).
Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):
nitrile rubber (NBR; >= 0.4 mm thickness)
Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):
nitrile rubber (NBR; >= 0.4 mm thickness)
This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:
Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.
Protective eye equipment should conform to EN166.

Skin protection:
Wear suitable protective clothing.
Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:
The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

## SECTION 9: Physical and chemical properties

**9.1. Information on basic physical and chemical properties**

| | |
|---|---|
| Delivery form | liquid |
| Colour | Brown |
| Odor | Mild |
| Physical state | liquid |
| Melting point | Not applicable, Product is a liquid |
| Solidification temperature | < -30 °C (< -22 °F) |
| Initial boiling point | > 150 °C (> 302 °F) |
| Flammability | The product is not flammable. |
| Explosive limits | Not applicable, The product is not flammable. |
| Flash point | > 100 °C (> 212 °F) No flash point up to 100 °C |
| Auto-ignition temperature | > 300 °C (> 572 °F) |
| Decomposition temperature | Not applicable, Substance/mixture is not self-reactive, no organic peroxide and does not decompose under foreseen conditions of use |
| pH | Not applicable, Product is non-polar/aprotic. |
| Viscosity (kinematic)<br>(40 °C (104 °F); ) | > 20,5 mm2/s |
| Solubility (qualitative)<br>(20 °C (68 °F); Solvent: Water) | Slight |
| Solubility (qualitative) | Not miscible |

| | |
|---|---|
| (Solvent: Water) | |
| Partition coefficient: n-octanol/water | Not applicable<br>Mixture |
| Vapour pressure<br>(27 °C (80.6 °F)) | < 5 mm hg |
| Vapour pressure<br>(50 °C (122 °F)) | < 300 mbar;no method / method unknown |
| Vapour pressure<br>(20 °C (68 °F)) | < 1 mm hg |
| Density<br>(20 °C (68 °F)) | 1,08 g/cm3 None |
| Relative vapour density:<br>(20 °C) | > 1 |
| Particle characteristics | Not applicable<br>Product is a liquid |

**9.2. Other information**

Other information not applicable for this product

## SECTION 10: Stability and reactivity

**10.1. Reactivity**
Reacts with strong oxidants.
Acids.
Reducing agents.
Strong bases.

**10.2. Chemical stability**
Stable under recommended storage conditions.

**10.3. Possibility of hazardous reactions**
See section reactivity

**10.4. Conditions to avoid**
Stable under normal conditions of storage and use.

**10.5. Incompatible materials**
See section reactivity.

**10.6. Hazardous decomposition products**
carbon oxides.
Hydrocarbons
nitrogen oxides
Rapid polymerisation may generate excessive heat and pressure.

## SECTION 11: Toxicological information

**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

**Acute oral toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

| Hazardous substances<br>CAS-No. | Value type | Value | Species | Method |
|---|---|---|---|---|
| Cumene hydroperoxide<br>80-15-9 | LD50 | 382 mg/kg | rat | other guideline: |
| N,N-Diethyl-p-toluidine<br>613-48-9 | Acute toxicity estimate (ATE) | 100 mg/kg | | Expert judgement |
| N,N-dimethyl-o-toluidine<br>609-72-3 | Acute toxicity estimate (ATE) | 100 mg/kg | | Expert judgement |
| methacrylic acid<br>79-41-4 | LD50 | 1.320 mg/kg | rat | equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity) |
| 1,4-Naphthalenedione<br>130-15-4 | LD50 | 124 mg/kg | rat | equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity) |

**Acute dermal toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

| Hazardous substances<br>CAS-No. | Value type | Value | Species | Method |
|---|---|---|---|---|
| Cumene hydroperoxide<br>80-15-9 | Acute toxicity estimate (ATE) | 1.100 mg/kg | | Expert judgement |
| N,N-Diethyl-p-toluidine<br>613-48-9 | Acute toxicity estimate (ATE) | 300 mg/kg | | Expert judgement |
| N,N-dimethyl-o-toluidine<br>609-72-3 | Acute toxicity estimate (ATE) | 300 mg/kg | | Expert judgement |
| methacrylic acid<br>79-41-4 | LD50 | 500 - 1.000 mg/kg | rabbit | Dermal Toxicity Screening |
| methacrylic acid<br>79-41-4 | Acute toxicity estimate (ATE) | 500 mg/kg | | Expert judgement |

**Acute inhalative toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

| Hazardous substances<br>CAS-No. | Value type | Value | Test atmosphere | Exposure time | Species | Method |
|---|---|---|---|---|---|---|
| Cumene hydroperoxide<br>80-15-9 | LC50 | 1,370 mg/l | vapour | 4 h | rat | not specified |
| N,N-Diethyl-p-toluidine<br>613-48-9 | Acute toxicity estimate (ATE) | 3 mg/l | vapour | | | Expert judgement |
| N,N-dimethyl-o-toluidine<br>609-72-3 | Acute toxicity estimate (ATE) | 0,5 mg/l | dust/mist | 4 h | | Expert judgement |
| methacrylic acid<br>79-41-4 | LC50 | 3,19 - 6,5 mg/l | dust/mist | 4 h | rat | equivalent or similar to OECD Guideline 403 (Acute Inhalation Toxicity) |
| methacrylic acid<br>79-41-4 | Acute toxicity estimate (ATE) | 3,19 mg/l | dust/mist | | | Expert judgement |
| 1,4-Naphthalenedione<br>130-15-4 | LC50 | 0,046 mg/l | dust/mist | 4 h | rat | OECD Guideline 403 (Acute Inhalation Toxicity) |

**Skin corrosion/irritation:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

| Hazardous substances<br>CAS-No. | Result | Exposure time | Species | Method |
|---|---|---|---|---|
| Cumene hydroperoxide<br>80-15-9 | corrosive | | rabbit | Draize Test |
| N,N-Diethyl-p-toluidine<br>613-48-9 | irritating | 4 h | rabbit | OECD Guideline 404 (Acute Dermal Irritation / Corrosion) |
| methacrylic acid<br>79-41-4 | corrosive | 3 min | rabbit | OECD Guideline 404 (Acute Dermal Irritation / Corrosion) |
| 1,4-Naphthalenedione<br>130-15-4 | Category 1C (corrosive) | | rabbit | OECD Guideline 404 (Acute Dermal Irritation / Corrosion) |

**Serious eye damage/irritation:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances<br>CAS-No. | Result | Exposure time | Species | Method |
|---|---|---|---|---|
| methacrylic acid<br>79-41-4 | corrosive | | rabbit | Draize Test |

**Respiratory or skin sensitization:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

| Hazardous substances<br>CAS-No. | Result | Test type | Species | Method |
|---|---|---|---|---|
| methacrylic acid<br>79-41-4 | not sensitising | Buehler test | guinea pig | equivalent or similar to OECD Guideline 406 (Skin Sensitisation) |
| 1,4-Naphthalenedione<br>130-15-4 | sensitising | not specified | guinea pig | not specified |

**Germ cell mutagenicity:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

| Hazardous substances<br>CAS-No. | Result | Type of study /<br>Route of administration | Metabolic activation /<br>Exposure time | Species | Method |
|---|---|---|---|---|---|
| Cumene hydroperoxide<br>80-15-9 | positive | bacterial reverse mutation assay (e.g Ames test) | without | | OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| methacrylic acid<br>79-41-4 | negative | bacterial reverse mutation assay (e.g Ames test) | with and without | | equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay) |

**Carcinogenicity**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

| Hazardous components<br>CAS-No. | Result | Route of application | Exposure time /<br>Frequency of treatment | Species | Sex | Method |
|---|---|---|---|---|---|---|
| methacrylic acid<br>79-41-4 | not carcinogenic | inhalation | 2 y | mouse | male/female | OECD Guideline 451 (Carcinogenicity Studies) |

**Reproductive toxicity:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

| Hazardous substances<br>CAS-No. | Result / Value | Test type | Route of application | Species | Method |
|---|---|---|---|---|---|
| methacrylic acid<br>79-41-4 | NOAEL P 50 mg/kg<br><br>NOAEL F1 400 mg/kg<br><br>NOAEL F2 400 mg/kg | Two generation study | oral: gavage | rat | OECD Guideline 416 (Two-Generation Reproduction Toxicity Study) |

**STOT-single exposure:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances<br>CAS-No. | Assessment | Route of exposure | Target Organs | Remarks |
|---|---|---|---|---|
| methacrylic acid<br>79-41-4 | May cause respiratory irritation. | | | |

**STOT-repeated exposure:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

| Hazardous substances<br>CAS-No. | Result / Value | Route of application | Exposure time /<br>Frequency of treatment | Species | Method |
|---|---|---|---|---|---|
| Cumene hydroperoxide<br>80-15-9 | | inhalation: aerosol | 6 h/d<br>5 d/w | rat | not specified |
| methacrylic acid<br>79-41-4 | | inhalation | 90 d<br>6 h/d, 5 d/w | rat | OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day) |

**Aspiration hazard:**

No data available.

**11.2 Information on other hazards**

not applicable

## SECTION 12: Ecological information

**General ecological information:**
Do not empty into drains / surface water / ground water.

### 12.1. Toxicity

**Toxicity (Fish):**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

| Hazardous substances<br>CAS-No. | Value type | Value | Exposure time | Species | Method |
|---|---|---|---|---|---|
| Cumene hydroperoxide<br>80-15-9 | LC50 | 3,9 mg/l | 96 h | Oncorhynchus mykiss | OECD Guideline 203 (Fish, Acute Toxicity Test) |
| N,N-Diethyl-p-toluidine<br>613-48-9 | LC50 | 78,62 mg/l | 96 h | Danio rerio | OECD Guideline 203 (Fish, Acute Toxicity Test) |
| N,N-dimethyl-o-toluidine<br>609-72-3 | LC50 | 46 mg/l | 96 h | Pimephales promelas | OECD Guideline 203 (Fish, Acute Toxicity Test) |
| methacrylic acid<br>79-41-4 | LC50 | 85 mg/l | 96 h | Salmo gairdneri (new name: Oncorhynchus mykiss) | EPA OTS 797.1400 (Fish Acute Toxicity Test) |
| methacrylic acid<br>79-41-4 | NOEC | 10 mg/l | 35 d | Danio rerio | OECD Guideline 210 (fish early lite stage toxicity test) |
| 1,4-Naphthalenedione<br>130-15-4 | LC50 | 0,045 mg/l | 96 h | Oryzias latipes | OECD Guideline 203 (Fish, Acute Toxicity Test) |

**Toxicity (aquatic invertebrates):**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

| Hazardous substances<br>CAS-No. | Value type | Value | Exposure time | Species | Method |
|---|---|---|---|---|---|
| Cumene hydroperoxide<br>80-15-9 | EC50 | 18,84 mg/l | 48 h | Daphnia magna | OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test) |
| N,N-Diethyl-p-toluidine<br>613-48-9 | EC50 | 10,34 mg/l | 48 h | Daphnia magna | OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test) |
| methacrylic acid<br>79-41-4 | EC50 | > 130 mg/l | 48 h | Daphnia magna | EPA OTS 797.1300 (Aquatic Invertebrate Acute Toxicity Test, Freshwater Daphnids) |
| 1,4-Naphthalenedione<br>130-15-4 | EC50 | 0,026 mg/l | 48 h | Daphnia magna | OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test) |

**Chronic toxicity (aquatic invertebrates):**

The table below presents the data of the classified substances present in the mixture.

| Hazardous substances<br>CAS-No. | Value type | Value | Exposure time | Species | Method |
|---|---|---|---|---|---|
| methacrylic acid<br>79-41-4 | NOEC | 53 mg/l | 21 d | Daphnia magna | OECD 211 (Daphnia magna, Reproduction Test) |

**Toxicity (Algae):**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

| Hazardous substances<br>CAS-No. | Value type | Value | Exposure time | Species | Method |
|---|---|---|---|---|---|
| Cumene hydroperoxide<br>80-15-9 | EC50 | 3,1 mg/l | 72 h | Desmodesmus subspicatus (reported as Scenedesmus subspicatus) | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| Cumene hydroperoxide<br>80-15-9 | NOEC | 1 mg/l | 72 h | Desmodesmus subspicatus (reported as Scenedesmus subspicatus) | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| N,N-Diethyl-p-toluidine<br>613-48-9 | EC50 | 23,69 mg/l | 72 h | Raphidocelis subcapitata (new name: Pseudokirchneriella subcapitata) | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| methacrylic acid<br>79-41-4 | NOEC | 8,2 mg/l | 72 h | Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata) | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| methacrylic acid<br>79-41-4 | EC50 | 45 mg/l | 72 h | Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata) | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| 1,4-Naphthalenedione<br>130-15-4 | NOEC | 0,07 mg/l | 72 h | Pseudokirchneriella subcapitata | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| 1,4-Naphthalenedione<br>130-15-4 | EC50 | 0,42 mg/l | 72 h | Pseudokirchneriella subcapitata | OECD Guideline 201 (Alga, Growth Inhibition Test) |

**Toxicity (microorganisms):**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

| Hazardous substances<br>CAS-No. | Value type | Value | Exposure time | Species | Method |
|---|---|---|---|---|---|
| Cumene hydroperoxide<br>80-15-9 | EC10 | 70 mg/l | 30 min | not specified | not specified |
| methacrylic acid<br>79-41-4 | EC10 | 100 mg/l | 17 h | Pseudomonas putida | DIN 38412, part 8 (Pseudomonas Zellvermehrungshemm-Test) |
| 1,4-Naphthalenedione<br>130-15-4 | EC50 | 5,94 mg/l | 3 h | activated sludge of a predominantly domestic sewage | OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test) |

**12.2. Persistence and degradability**

The table below presents the data of the classified substances present in the mixture.

| Hazardous substances<br>CAS-No. | Result | Test type | Degradability | Exposure time | Method |
|---|---|---|---|---|---|
| Cumene hydroperoxide<br>80-15-9 | not readily biodegradable. | aerobic | 3 % | 28 d | OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test) |
| N,N-Diethyl-p-toluidine<br>613-48-9 | not readily biodegradable. | not specified | 1 % | 28 day | OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I)) |
| N,N-dimethyl-o-toluidine<br>609-72-3 | not readily biodegradable. | aerobic | 1 % | 14 d | other guideline: |
| methacrylic acid<br>79-41-4 | readily biodegradable | aerobic | 86 % | 28 d | OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test) |
| methacrylic acid<br>79-41-4 | inherently biodegradable | aerobic | 100 % | 14 d | OECD Guideline 302 B (Inherent biodegradability: Zahn-Wellens/EMPA Test) |
| 1,4-Naphthalenedione<br>130-15-4 | not readily biodegradable. | aerobic | 0 % | 28 d | OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test) |

**12.3. Bioaccumulative potential**

The table below presents the data of the classified substances present in the mixture.

| Hazardous substances<br>CAS-No. | Bioconcentration factor (BCF) | Exposure time | Temperature | Species | Method |
|---|---|---|---|---|---|
| Cumene hydroperoxide<br>80-15-9 | 9,1 | | | calculation | OECD Guideline 305 (Bioconcentration: Flow-through Fish Test) |

**12.4. Mobility in soil**

The table below presents the data of the classified substances present in the mixture.

| Hazardous substances<br>CAS-No. | LogPow | Temperature | Method |
|---|---|---|---|
| Cumene hydroperoxide<br>80-15-9 | 1,6 | 25 °C | OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method) |
| N,N-Diethyl-p-toluidine<br>613-48-9 | 3,7 | | QSAR (Quantitative Structure Activity Relationship) |
| methacrylic acid<br>79-41-4 | 0,93 | 22 °C | OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method) |
| 1,4-Naphthalenedione<br>130-15-4 | 1,71 | | not specified |

**12.5. Results of PBT and vPvB assessment**

The table below presents the data of the classified substances present in the mixture.

| Hazardous substances<br>CAS-No. | PBT / vPvB |
|---|---|
| Cumene hydroperoxide<br>80-15-9 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |
| methacrylic acid<br>79-41-4 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |
| 1,4-Naphthalenedione<br>130-15-4 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |

**12.6. Endocrine disrupting properties**

not applicable

**12.7. Other adverse effects**

No data available.

## SECTION 13: Disposal considerations

**13.1. Waste treatment methods**

Product disposal:
Do not empty into drains / surface water / ground water.
Dispose of in accordance with local and national regulations.

Disposal of uncleaned packages:
After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Waste code

08 04 09* waste adhesives and sealants containing organic solvents and other dangerous substances
The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

## SECTION 14: Transport information

**14.1. UN number or ID number**

| | |
|---|---|
| ADR | Not dangerous goods |
| RID | Not dangerous goods |
| ADN | Not dangerous goods |
| IMDG | Not dangerous goods |
| IATA | Not dangerous goods |

**14.2. UN proper shipping name**

| | |
|---|---|
| ADR | Not dangerous goods |
| RID | Not dangerous goods |
| ADN | Not dangerous goods |
| IMDG | Not dangerous goods |
| IATA | Not dangerous goods |

**14.3. Transport hazard class(es)**

| | |
|---|---|
| ADR | Not dangerous goods |
| RID | Not dangerous goods |
| ADN | Not dangerous goods |
| IMDG | Not dangerous goods |
| IATA | Not dangerous goods |

**14.4. Packing group**

| | |
|---|---|
| ADR | Not dangerous goods |
| RID | Not dangerous goods |
| ADN | Not dangerous goods |
| IMDG | Not dangerous goods |
| IATA | Not dangerous goods |

**14.5. Environmental hazards**

| | |
|---|---|
| ADR | not applicable |
| RID | not applicable |
| ADN | not applicable |
| IMDG | not applicable |
| IATA | not applicable |

**14.6. Special precautions for user**

| | |
|---|---|
| ADR | not applicable |
| RID | not applicable |
| ADN | not applicable |
| IMDG | not applicable |
| IATA | not applicable |

**14.7. Maritime transport in bulk according to IMO instruments**

not applicable

## SECTION 15: Regulatory information

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

| | |
|---|---|
| Ozone Depleting Substance (ODS) (Regulation (EC) No 2024/590): | Not applicable |
| Prior Informed Consent (PIC) (Regulation (EU) No 649/2012): | Not applicable |
| Persistent organic pollutants (Regulation (EU) 2019/1021): | Not applicable |
| VOC content | < 5 % |

(2010/75/EC)

**15.2. Chemical safety assessment**

A chemical safety assessment has not been carried out.

## SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text
of all abbreviations indicated by codes in this safety data sheet are as follows:

H242 Heating may cause a fire.
H301 Toxic if swallowed.
H302 Harmful if swallowed.
H311 Toxic in contact with skin.
H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H330 Fatal if inhaled.
H331 Toxic if inhaled.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H373 May cause damage to organs through prolonged or repeated exposure.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

| | |
|---|---|
| ED: | Substance identified as having endocrine disrupting properties |
| EU OEL: | Substance with a Union workplace exposure limit |
| EU EXPLD 1: | Substance listed in Annex I, Reg (EC) No. 2019/1148 |
| EU EXPLD 2 | Substance listed in Annex II, Reg (EC) No. 2019/1148 |
| SVHC: | Substance of very high concern (REACH Candidate List) |
| PBT: | Substance fulfilling persistent, bioaccumulative and toxic criteria |
| PBT/vPvB: | Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very bioaccumulative criteria |
| vPvB: | Substance fulfilling very persistent and very bioaccumulative criteria |

**Further information:**

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel´s Product Safety and Regulatory Affairs Department (SDSinfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,
Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Dear Customer,
Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

**Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.**