Safety Data Sheet according to (EC) No 1907/2006 as amended

SDS No. : 173071
V013.0

LOCTITE SF 7200 400ML EGFD

Revision: 10.09.2025
printing date: 11.09.2025
Replaces version from: 23.10.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

LOCTITE SF 7200 400ML EGFD
UFI: 10SY-GVSX-Y20R-QVFJ

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:
Solvent based cleaner

1.3. Details of the supplier of the safety data sheet

Henkel Ltd
Adhesives
Wood Lane End
HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (1442) 278000

SDSinfo.Adhesive@henkel.com
For Safety Data Sheet updates please visit our website www.mysds.henkel.com or www.henkel-adhesives.com.

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Flammable aerosols	Category 1
H222 Extremely flammable aerosol.	
H229 Pressurized container: May burst if heated.	
Skin irritation	Category 2
H315 Causes skin irritation.	
Serious eye irritation	Category 2
H319 Causes serious eye irritation.	

2.2. Label elements

Label elements (CLP):

Hazard pictogram:



Signal word:	Danger
Hazard statement:	H222 Extremely flammable aerosol. H229 Pressurized container: May burst if heated. H315 Causes skin irritation. H319 Causes serious eye irritation.
Precautionary statement:	P102 Keep out of reach of children. "***" ***For consumer use only: P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P501 Dispose of contents/container in accordance with national regulation.***
Precautionary statement: Prevention	P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use.
Precautionary statement: Response	P302+P352 IF ON SKIN: Wash with plenty of soap and water. P337+P313 If eye irritation persists: Get medical advice/attention.
Precautionary statement: Storage	P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

2.3. Other hazards

None if used properly.

Following substances are present in a concentration ≥ the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in a concentration ≥ the concentration limit for depiction in Section 3 that are assessed to be a PBT, vPvB or ED.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS No. EC No. REACH-Reg. No.	Concentration	Classification	Specific Conc. Limits, M-factors and ATEs	Add. Information
Methylal 109-87-5 203-714-2 01-2119664781-31	50- < 75 %	Flam. Liq. 2, H225		
Propane 74-98-6 200-827-9 01-2119486944-21	10- < 25 %	Flam. Gas 1A, H220 Press. Gas H280		
1,3-Dioxolane 646-06-0 211-463-5 01-2119490744-29	2,5- < 10 %	Flam. Liq. 2, H225 Eye Dam. 1, H318		
Propan-2-ol 67-63-0 200-661-7 01-2119457558-25	2,5- < 10 %	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336		
Ethanol 64-17-5 200-578-6 01-2119457610-43	2,5- < 10 %	Eye Irrit. 2, H319 Flam. Liq. 2, H225	Eye Irrit. 2; H319; C >= 50 %	
Butane, n- (< 0.1 % butadiene) 106-97-8 203-448-7 01-2119474691-32	1- < 2,5 %	Press. Gas H280 Flam. Gas 1A, H220		
Butanone 78-93-3 201-159-0 01-2119457290-43	1- < 2,5 %	STOT SE 3, H336 Eye Irrit. 2, H319 Flam. Liq. 2, H225		EU OEL
2-aminoethanol 141-43-5 205-483-3 01-2119486455-28	1- < 2,5 %	Acute Tox. 4, Oral, H302 Acute Tox. 4, Dermal, H312 Eye Dam. 1, H318 Skin Corr. 1B, H314 Acute Tox. 4, Inhalation, H332 STOT SE 3, H335 Aquatic Chronic 3, H412	STOT SE 3; H335; C >= 5 % ===== inhalation:ATE = 1,5 mg/l;dust/mist	EU OEL
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatic ----- 01-2119457273-39	1- < 2,5 %	Asp. Tox. 1, H304		

If no ATE values are displayed, please refer to LD/LC50 values in Section 11.
For full text of the H - statements and other abbreviations see section 16 "Other information".

The hazard classification of this product is based solely on the mixture present within the aerosol, excluding the propellant gases. The information provided in Section 3 is based on the combination of the mixture and propellant gases.

Declaration of ingredients according to Detergent Regulation 648/2004/EC

15 - 30 %	aliphatic hydrocarbons
< 5 %	non-ionic surfactants

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:
Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:
Rinse with running water and soap.
Obtain medical attention if irritation persists.

Eye contact:
Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:
Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed
SKIN: Redness, inflammation.

EYE: Irritation, conjunctivitis.

4.3. Indication of any immediate medical attention and special treatment needed
See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media
Suitable extinguishing media:
water, carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons:
High pressure waterjet

5.2. Special hazards arising from the substance or mixture
In the event of a fire, carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx) can be released.

5.3. Advice for firefighters
Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional information:
In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures
Avoid contact with skin and eyes.
Wear protective equipment.
Ensure adequate ventilation.
Keep away from sources of ignition.

6.2. Environmental precautions
Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up
Dispose of contaminated material as waste according to Section 13.
For small spills wipe up with paper towel and place in container for disposal.
For large spills absorb onto inert absorbent material and place in sealed container for disposal.

6.4. Reference to other sections
See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid skin and eye contact.
See advice in section 8

Hygiene measures:

Good industrial hygiene practices should be observed.
Wash hands before work breaks and after finishing work.
Do not eat, drink or smoke while working.

7.2. Conditions for safe storage, including any incompatibilities

Ensure good ventilation/extraction.
Store in a cool, dry place.
Do not store near sources of heat or ignition, or reactive materials.
Refer to Technical Data Sheet.

7.3. Specific end use(s)

Solvent based cleaner

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for
Great Britain

Ingredient [Regulated substance]	ppm	mg/m³	Value type	Short term exposure limit category / Remarks	Regulatory list
Dimethoxymethane 109-87-5 [DIMETHOXYMETHANE]	1.000	3.160	Time Weighted Average (TWA):		EH40 WEL
Dimethoxymethane 109-87-5 [DIMETHOXYMETHANE]	1.250	3.950	Short Term Exposure Limit (STEL):	15 minutes	EH40 WEL
Propan-2-ol 67-63-0 [PROPAN-2-OL]	400	999	Time Weighted Average (TWA):		EH40 WEL
Propan-2-ol 67-63-0 [PROPAN-2-OL]	500	1.250	Short Term Exposure Limit (STEL):	15 minutes	EH40 WEL
Ethanol 64-17-5 [ETHANOL]	1.000	1.920	Time Weighted Average (TWA):		EH40 WEL
Butane 106-97-8 [Butane]	600	1.450	Time Weighted Average (TWA):		EH40 WEL
Butane 106-97-8 [Butane]	750	1.810	Short Term Exposure Limit (STEL):	15 minutes	EH40 WEL
Butanone 78-93-3 [BUTAN-2-ONE (METHYL ETHYL KETONE)]			Skin designation:	Can be absorbed through the skin.	EH40 WEL
Butanone 78-93-3 [BUTAN-2-ONE (METHYL ETHYL KETONE)]	200	600	Time Weighted Average (TWA):		EH40 WEL
Butanone 78-93-3 [BUTANONE]	200	600	Time Weighted Average (TWA):	Indicative	ECTLV
Butanone 78-93-3 [BUTANONE]	300	900	Short Term Exposure Limit (STEL):	Indicative	ECTLV
Butanone 78-93-3 [BUTAN-2-ONE (METHYL ETHYL KETONE)]	300	899	Short Term Exposure Limit (STEL):	15 minutes	EH40 WEL
2-Aminoethanol 141-43-5 [2-AMINOETHANOL]			Skin designation:	Can be absorbed through the skin.	EH40 WEL
2-Aminoethanol 141-43-5 [2-AMINOETHANOL]	1	2,5	Time Weighted Average (TWA):		EH40 WEL
2-Aminoethanol 141-43-5 [2-AMINOETHANOL]	3	7,6	Short Term Exposure Limit (STEL):	Indicative	ECTLV
2-Aminoethanol 141-43-5 [2-AMINOETHANOL]	1	2,5	Time Weighted Average (TWA):	Indicative	ECTLV
2-Aminoethanol 141-43-5 [2-AMINOETHANOL]	3	7,6	Short Term Exposure Limit (STEL):	15 minutes	EH40 WEL
2-Aminoethanol 141-43-5 [2-Aminoethanol]			Skin designation:	Can be absorbed through the skin.	ECTLV

Occupational Exposure Limits

Valid for
Ireland

Ingredient [Regulated substance]	ppm	mg/m³	Value type	Short term exposure limit category / Remarks	Regulatory list
Dimethoxymethane 109-87-5 [METHYLAL]	1.000	3.100	Time Weighted Average (TWA):		IR_OEL
1,3-Dioxolane 646-06-0 [1,3-DIOXOLANE]	20		Time Weighted Average (TWA):		IR_OEL
Propan-2-ol 67-63-0 [ISOPROPYL ALCOHOL]	200		Time Weighted Average (TWA):		IR_OEL
Propan-2-ol 67-63-0 [ISOPROPYL ALCOHOL]			Skin designation:	Can be absorbed through the skin.	IR_OEL
Propan-2-ol 67-63-0 [ISOPROPYL ALCOHOL]	400		Short Term Exposure Limit (STEL):	15 minutes	IR_OEL
Ethanol 64-17-5 [ETHANOL]	1.000		Short Term Exposure Limit (STEL):	15 minutes	IR_OEL
Butane 106-97-8 [N-BUTANE]	1.000		Short Term Exposure Limit (STEL):	15 minutes	IR_OEL
Butanone 78-93-3 [METHYL ETHYL KETONE (MEK)]	200	600	Time Weighted Average (TWA):	Indicative OELV	IR_OEL
Butanone 78-93-3 [METHYL ETHYL KETONE (MEK)]			Skin designation:	Can be absorbed through the skin.	IR_OEL
Butanone 78-93-3 [BUTANONE]	200	600	Time Weighted Average (TWA):	Indicative	ECTLV
Butanone 78-93-3 [BUTANONE]	300	900	Short Term Exposure Limit (STEL):	Indicative	ECTLV
Butanone 78-93-3 [METHYL ETHYL KETONE (MEK)]	300	900	Short Term Exposure Limit (STEL):	15 minutes Indicative OELV	IR_OEL
2-Aminoethanol 141-43-5 [2-AMINOETHANOL]	3	7,6	Short Term Exposure Limit (STEL):	Indicative	ECTLV
2-Aminoethanol 141-43-5 [2-AMINOETHANOL]	1	2,5	Time Weighted Average (TWA):	Indicative	ECTLV
2-Aminoethanol 141-43-5 [2-AMINOETHANOL]			Skin designation:	Can be absorbed through the skin.	IR_OEL
2-Aminoethanol 141-43-5 [2-AMINOETHANOL]	3	7,6	Short Term Exposure Limit (STEL):	15 minutes Indicative OELV	IR_OEL
2-Aminoethanol 141-43-5 [2-Aminoethanol]			Skin designation:	Can be absorbed through the skin.	ECTLV
2-Aminoethanol 141-43-5 [2-Aminoethanol]	1	2,5	Time Weighted Average (TWA):	Indicative OELV	IR_OEL

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
Dimethoxymethane 109-87-5	aqua (freshwater)		14,577 mg/l				
Dimethoxymethane 109-87-5	aqua (marine water)		1,4577 mg/l				
Dimethoxymethane 109-87-5	sediment (freshwater)				13,135 mg/kg		
Dimethoxymethane 109-87-5	sediment (marine water)				1,3135 mg/kg		
Dimethoxymethane 109-87-5	Soil				4,6538 mg/kg		
Dimethoxymethane 109-87-5	Sewage treatment plant		10000 mg/l				
1,3-Dioxolane 646-06-0	aqua (freshwater)		19,7 mg/l				
1,3-Dioxolane 646-06-0	aqua (intermittent releases)		0,95 mg/l				
1,3-Dioxolane 646-06-0	aqua (marine water)		1,97 mg/l				
1,3-Dioxolane 646-06-0	sewage treatment plant (STP)		100 mg/l				
1,3-Dioxolane 646-06-0	sediment (freshwater)				77,7 mg/kg		
1,3-Dioxolane 646-06-0	sediment (marine water)				7,77 mg/kg		
1,3-Dioxolane 646-06-0	Soil				2,62 mg/kg		
Propan-2-ol 67-63-0	aqua (freshwater)		140,9 mg/l				
Propan-2-ol 67-63-0	aqua (marine water)		140,9 mg/l				
Propan-2-ol 67-63-0	sediment (freshwater)				552 mg/kg		
Propan-2-ol 67-63-0	sediment (marine water)				552 mg/kg		
Propan-2-ol 67-63-0	Soil				28 mg/kg		
Propan-2-ol 67-63-0	aqua (intermittent releases)		140,9 mg/l				
Propan-2-ol 67-63-0	sewage treatment plant (STP)		2251 mg/l				
Propan-2-ol 67-63-0	oral				160 mg/kg		
Ethanol 64-17-5	aqua (freshwater)		0,96 mg/l				
Ethanol 64-17-5	aqua (marine water)		0,79 mg/l				
Ethanol 64-17-5	aqua (intermittent releases)		2,75 mg/l				
Ethanol 64-17-5	sewage treatment plant (STP)		580 mg/l				
Ethanol 64-17-5	sediment (freshwater)				3,6 mg/kg		
Ethanol 64-17-5	sediment (marine water)				2,9 mg/kg		
Ethanol 64-17-5	Soil				0,63 mg/kg		
Ethanol 64-17-5	oral				380 mg/kg		
Butanone 78-93-3	aqua (freshwater)		55,8 mg/l				

Butanone 78-93-3	aqua (marine water)		55,8 mg/l				
Butanone 78-93-3	aqua (intermittent releases)		55,8 mg/l				
Butanone 78-93-3	sewage treatment plant (STP)		709 mg/l				
Butanone 78-93-3	sediment (freshwater)				284,74 mg/kg		
Butanone 78-93-3	sediment (marine water)				284,7 mg/kg		
Butanone 78-93-3	Soil				22,5 mg/kg		
Butanone 78-93-3	oral				1000 mg/kg		
2-Aminoethanol 141-43-5	aqua (freshwater)		0,07 mg/l				
2-Aminoethanol 141-43-5	aqua (marine water)		0,007 mg/l				
2-Aminoethanol 141-43-5	aqua (intermittent releases)		0,028 mg/l				
2-Aminoethanol 141-43-5	sediment (freshwater)				0,357 mg/kg		
2-Aminoethanol 141-43-5	sediment (marine water)				0,036 mg/kg		
2-Aminoethanol 141-43-5	Soil				1,29 mg/kg		
2-Aminoethanol 141-43-5	sewage treatment plant (STP)		100 mg/l				

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Dimethoxymethane 109-87-5	Workers	dermal	Long term exposure - systemic effects		17,9 mg/kg	
Dimethoxymethane 109-87-5	Workers	inhalation	Long term exposure - systemic effects		126,6 mg/m3	
Dimethoxymethane 109-87-5	General population	oral	Long term exposure - systemic effects		18,1 mg/kg	
Dimethoxymethane 109-87-5	General population	inhalation	Long term exposure - systemic effects		31,5 mg/m3	
Dimethoxymethane 109-87-5	General population	dermal	Long term exposure - systemic effects		18,1 mg/kg	
1,3-Dioxolane 646-06-0	Workers	inhalation	Long term exposure - systemic effects		3,26 mg/m3	
1,3-Dioxolane 646-06-0	Workers	dermal	Long term exposure - systemic effects		0,93 mg/kg	
1,3-Dioxolane 646-06-0	General population	inhalation	Long term exposure - systemic effects		1,48 mg/m3	
1,3-Dioxolane 646-06-0	General population	oral	Long term exposure - systemic effects		0,33 mg/kg	
1,3-Dioxolane 646-06-0	General population	dermal	Long term exposure - systemic effects		0,33 mg/kg	
Propan-2-ol 67-63-0	Workers	dermal	Long term exposure - systemic effects		888 mg/kg	
Propan-2-ol 67-63-0	Workers	inhalation	Long term exposure - systemic effects		500 mg/m3	
Propan-2-ol 67-63-0	General population	dermal	Long term exposure - systemic effects		319 mg/kg	
Propan-2-ol 67-63-0	General population	inhalation	Long term exposure - systemic effects		89 mg/m3	
Propan-2-ol 67-63-0	General population	oral	Long term exposure - systemic effects		26 mg/kg	
Ethanol 64-17-5	Workers	dermal	Long term exposure - systemic effects		343 mg/kg	
Ethanol 64-17-5	Workers	inhalation	Long term exposure - systemic effects		950 mg/m3	
Ethanol 64-17-5	General population	dermal	Long term exposure - systemic effects		206 mg/kg	
Ethanol 64-17-5	General population	inhalation	Long term exposure - systemic effects		114 mg/m3	
Ethanol 64-17-5	General population	oral	Long term exposure - systemic effects		87 mg/kg	
Butanone 78-93-3	Workers	dermal	Long term exposure - systemic effects		1161 mg/kg	
Butanone 78-93-3	Workers	inhalation	Long term exposure - systemic effects		600 mg/m3	
Butanone 78-93-3	General population	dermal	Long term exposure -		412 mg/kg	

			systemic effects			
Butanone 78-93-3	General population	inhalation	Long term exposure - systemic effects		106 mg/m3	
Butanone 78-93-3	General population	oral	Long term exposure - systemic effects		31 mg/kg	
2-Aminoethanol 141-43-5	Workers	inhalation	Long term exposure - systemic effects		1 mg/m3	
2-Aminoethanol 141-43-5	Workers	inhalation	Long term exposure - local effects		0,51 mg/m3	
2-Aminoethanol 141-43-5	Workers	dermal	Long term exposure - systemic effects		3 mg/kg	
2-Aminoethanol 141-43-5	General population	dermal	Long term exposure - systemic effects		1,5 mg/kg	
2-Aminoethanol 141-43-5	General population	oral	Long term exposure - systemic effects		1,5 mg/kg	
2-Aminoethanol 141-43-5	General population	inhalation	Long term exposure - systemic effects		0,18 mg/m3	
2-Aminoethanol 141-43-5	General population	inhalation	Long term exposure - local effects		0,28 mg/m3	

Biological Exposure Indices:

Ingredient [Regulated substance]	Parameters	Biological specimen	Sampling time	Conc.	Basis of biol. exposure index	Remark	Additional Information
Butanone 78-93-3 [BUTAN-2-ONE]	Butan-2-one	Urine	Sampling time: End of shift.		UKEH40BMGV		

8.2. Exposure controls:

Engineering controls:
Ensure good ventilation/extraction.

Respiratory protection:
Ensure adequate ventilation.
An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area
Filter type: A (EN 14387)

Hand protection:
Chemical-resistant protective gloves (EN 374).
Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):
nitrile rubber (NBR; >= 0.4 mm thickness)
Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):
nitrile rubber (NBR; >= 0.4 mm thickness)
This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:
Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.
Protective eye equipment should conform to EN166.

Skin protection:
Wear suitable protective clothing.
Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:
The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Delivery form	aerosol
Colour	Amber
Odor	Alcohol
Physical state	liquid
Melting point	Not applicable, Product is a liquid
Initial boiling point	-44,5 °C (-48.1 °F)
Flammability	Extremely flammable aerosol.
Explosive limits	
lower	0,70 %(V);
upper	19,90 %(V);
	Upper/lower explosion limit
Flash point	-97 °C (-142.6 °F)
Auto-ignition temperature	Currently under determination
Decomposition temperature	Not applicable, Substance/mixture is not self-reactive, no organic peroxide and does not decompose under foreseen conditions of use
pH	Product is an aerosol. Concentrate is non-polar/aprotic., Not applicable
Viscosity (kinematic)	Not determined
Viscosity, dynamic	Not determined
()	
Solubility (qualitative)	Not miscible
(20 °C (68 °F); Solvent: Water)	
Solubility (qualitative)	Miscible
(20 °C (68 °F); Solvent: Acetone)	
Partition coefficient: n-octanol/water	Not applicable
	Mixture
Vapour pressure	Not determined
Density	0,79 g/cm3 None
(20 °C (68 °F))	
Relative vapour density:	Not available.
Particle characteristics	Not applicable
	Product is a liquid

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Aerosols:	Classified as Aerosol category 1 because it contains more than 1 % (by mass) flammable components or has a heat of combustion of at least 20 kJ/g and is not submitted to the flammability classification procedures

SECTION 10: Stability and reactivity

10.2. Chemical stability
Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions
See section reactivity

10.4. Conditions to avoid
Stable under normal conditions of storage and use.

10.5. Incompatible materials
None if used properly.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Methylal 109-87-5	LD50	6.423 mg/kg	rat	OECD Guideline 423 (Acute Oral toxicity)
1,3-Dioxolane 646-06-0	LD50	> 2.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
Propan-2-ol 67-63-0	LD50	5.840 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
Ethanol 64-17-5	LD50	10.470 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
Butanone 78-93-3	LD50	2.193 mg/kg	rat	OECD Guideline 423 (Acute Oral toxicity)
2-aminoethanol 141-43-5	LD50	1.089 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatic -----	LD50	> 15.000 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Methylal 109-87-5	LD50	> 5.000 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
1,3-Dioxolane 646-06-0	LD50	> 2.000 mg/kg	rabbit	not specified
Propan-2-ol 67-63-0	LD50	12.870 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
Ethanol 64-17-5	LD50	> 2.000 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
Butanone 78-93-3	LD50	> 6.400 mg/kg	rabbit	not specified
2-aminoethanol 141-43-5	LD50	1.025 mg/kg	rabbit	not specified
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatic -----	LD50	> 5.000 mg/kg	rabbit	equivalent or similar to OECD Guideline 402 (Acute Dermal Toxicity)

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
Methylal 109-87-5	LC50	15.000 mg/l	vapour	4 h	rat	not specified
Propane 74-98-6	LC50	> 800000 ppm	gas	15 min	rat	not specified
1,3-Dioxolane 646-06-0	LC50	68,4 mg/l	vapour	4 h	rat	equivalent or similar to OECD Guideline 403 (Acute Inhalation Toxicity)
Ethanol 64-17-5	LC50	124,7 mg/l	vapour	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)
Butane, n- (< 0.1 % butadiene) 106-97-8	LC50	274200 ppm	gas	4 h	rat	not specified
Butanone 78-93-3	LC50	34,5 mg/l	vapour	4 h	rat	not specified
2-aminoethanol 141-43-5	Acute toxicity estimate (ATE)	1,5 mg/l	dust/mist			Expert judgement
2-aminoethanol 141-43-5	LC50	1 - 5 mg/l		4 h	rat	not specified
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatic -----	LC50	> 5,6 mg/l	dust/mist	4 h	rat	equivalent or similar to OECD Guideline 403 (Acute Inhalation Toxicity)

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Methylal 109-87-5	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
1,3-Dioxolane 646-06-0	not irritating	24 h	rabbit	not specified
1,3-Dioxolane 646-06-0	not irritating		Human, EpiSkinTM (SM), Reconstructed Human Epidermis (RHE)	OECD Guideline 439 (In Vitro Skin Irritation: Reconstructed Human Epidermis (RHE) Test Method)
Propan-2-ol 67-63-0	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Ethanol 64-17-5	not irritating		rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Butanone 78-93-3	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
2-aminoethanol 141-43-5	corrosive		rabbit	equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
2-aminoethanol 141-43-5	corrosive	4 h	rabbit	equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
2-aminoethanol 141-43-5	corrosive		rabbit	equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatic -----	mildly irritating	4 h	rabbit	equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Methylal 109-87-5	not irritating		rabbit	equivalent or similar to OECD Guideline 405 (Acute Eye Irritation / Corrosion)
1,3-Dioxolane 646-06-0	Category 1 (irreversible effects on the eye)		Bovine, cornea, in vitro test	OECD Guideline 437 (BCOP)
Propan-2-ol 67-63-0	Category 2A (irritating to eyes)		rabbit	equivalent or similar to OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Ethanol 64-17-5	irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Butanone 78-93-3	irritating		rabbit	equivalent or similar to OECD Guideline 405 (Acute Eye Irritation / Corrosion)
2-aminoethanol 141-43-5	Category 1 (irreversible effects on the eye)		rabbit	equivalent or similar to OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Result	Test type	Species	Method
Methylal 109-87-5	not sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Propan-2-ol 67-63-0	not sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Ethanol 64-17-5	not sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Ethanol 64-17-5	not sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Butanone 78-93-3	not sensitising	Buehler test	guinea pig	equivalent or similar to OECD Guideline 406 (Skin Sensitisation)
2-aminoethanol 141-43-5	not sensitising	Guinea pig maximisation test	guinea pig	not specified

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Methylal 109-87-5	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Methylal 109-87-5	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Propane 74-98-6	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Propane 74-98-6	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Propan-2-ol 67-63-0	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Propan-2-ol 67-63-0	negative	mammalian cell gene mutation assay	with and without		equivalent or similar to OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Ethanol 64-17-5	negative	bacterial reverse mutation assay (e.g Ames test)			OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Ethanol 64-17-5	negative	in vitro mammalian chromosome aberration test	without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Ethanol 64-17-5	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Butane, n- (< 0.1 % butadiene) 106-97-8	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Butane, n- (< 0.1 % butadiene) 106-97-8	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Butanone 78-93-3	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Butanone 78-93-3	negative	in vitro mammalian chromosome aberration test	not applicable		equivalent or similar to OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Butanone 78-93-3	negative	mammalian cell gene mutation assay	with and without		equivalent or similar to OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
2-aminoethanol 141-43-5	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay)
2-aminoethanol 141-43-5	negative	in vitro mammalian chromosome aberration test	without		equivalent or similar to OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
2-aminoethanol 141-43-5	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)

Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
Propan-2-ol 67-63-0		inhalation: vapour	104 w 6 h/d, 5 d/w	rat	male/female	OECD Guideline 451 (Carcinogenicity Studies)
Ethanol 64-17-5	not carcinogenic					Expert judgement

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
Propane 74-98-6	NOAEL P 21,6 mg/l NOAEL F1 21,6 mg/l	screening	inhalation: gas	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Propan-2-ol 67-63-0	NOAEL P 853 mg/kg	One generation study	oral: drinking water	rat	equivalent or similar to OECD Guideline 415 (One-Generation Reproduction Toxicity Study)
Propan-2-ol 67-63-0	NOAEL P 500 mg/kg NOAEL F1 1.000 mg/kg	Two generation study	oral: gavage	rat	equivalent or similar to OECD Guideline 416 (Two-Generation Reproduction Toxicity Study)
Ethanol 64-17-5	NOAEL P 13.800 mg/kg	Two generation study	oral: unspecified	mouse	OECD Guideline 416 (Two-Generation Reproduction Toxicity Study)
Butane, n- (< 0.1 % butadiene) 106-97-8	NOAEL P 21,4 mg/l NOAEL F1 21,4 mg/l	screening	inhalation: gas	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Butanone 78-93-3	NOAEL P 10.000 mg/l NOAEL F1 10.000 mg/l	two-generation study	oral: drinking water	rat	equivalent or similar to OECD Guideline 416 (Two-Generation Reproduction Toxicity Study)
2-aminoethanol 141-43-5	NOAEL P 300 mg/kg NOAEL F1 1.000 mg/kg NOAEL F2 1.000 mg/kg	Two generation study	oral: feed	rat	OECD Guideline 416 (Two-Generation Reproduction Toxicity Study)

STOT-single exposure:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Assessment	Route of exposure	Target Organs	Remarks
Propan-2-ol 67-63-0	May cause drowsiness or dizziness.			
Butanone 78-93-3	May cause drowsiness or dizziness.			
2-aminoethanol 141-43-5	May cause respiratory irritation.			

STOT-repeated exposure:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
Methylal 109-87-5	NOAEL 6,3 mg/l	inhalation: vapour	13 weeks 6 h / d, 5 d / week	rat	OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day)
Propane 74-98-6		inhalation: gas	28 d 6 h/d, 7 d/w	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Propan-2-ol 67-63-0		inhalation: vapour	104 w 6 h/d, 5 d/w	rat	OECD Guideline 451 (Carcinogenicity Studies)
Butane, n- (< 0.1 % butadiene) 106-97-8		inhalation: gas	28 d 6 h/d	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Butanone 78-93-3	NOAEL 2500 ppm	inhalation	90 days 6 hours/day, 5 days/week	rat	not specified
2-aminoethanol 141-43-5	NOAEL 300 mg/kg	oral: feed	> 75 d daily	rat	other guideline:

Aspiration hazard:

The mixture is classified based on Viscosity data.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Viscosity (kinematic) Value	Temperature	Method	Remarks
Propan-2-ol 67-63-0	1,8 mm2/s	40 °C	ASTM Standard D7042	
Butanone 78-93-3	0,51 mm2/s	20 °C	ASTM Standard D7042	
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatic -----	1,13 mm2/s	40 °C	not specified	

11.2 Information on other hazards

not applicable

SECTION 12: Ecological information

General ecological information:
Do not empty into drains / surface water / ground water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Methylal 109-87-5	LC50	6.990 mg/l	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
1,3-Dioxolane 646-06-0	LC50	> 95,4 mg/l	96 h	Lepomis macrochirus	OECD Guideline 203 (Fish, Acute Toxicity Test)
Propan-2-ol 67-63-0	LC50	> 9.640 - 10.000 mg/l	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
Ethanol 64-17-5	LC50	14.200 mg/l	96 h	Pimephales promelas	EPA-660 (Methods for Acute Toxicity Tests with Fish, Macroinvertebrates and Amphibians)
Ethanol 64-17-5	NOEC	250 mg/l	120 h	Danio rerio	OECD Guideline 212 (Fish, Short-term Toxicity Test on Embryo and Sac-Fry Stages)
Butane, n- (< 0.1 % butadiene) 106-97-8	LC50	27,98 mg/l	96 h		QSAR (Quantitative Structure Activity Relationship)
Butanone 78-93-3	LC50	3.220 mg/l	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
2-aminoethanol 141-43-5	LC50	349 mg/l	96 h	Cyprinus carpio	EU Method C.1 (Acute Toxicity for Fish)
2-aminoethanol 141-43-5	NOEC	1,24 mg/l	41 d	Oryzias latipes	OECD Guideline 210 (fish early lite stage toxicity test)
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatic -----	LL50	> 1.000 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)

Toxicity (aquatic invertebrates):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Methylal 109-87-5	EC50	> 500 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
1,3-Dioxolane 646-06-0	EC50	> 772 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Ethanol 64-17-5	EC50	5.012 mg/l	48 h	Ceriodaphnia dubia	other guideline:
Butane, n- (< 0.1 % butadiene) 106-97-8	EC50	14,22 mg/l	48 h		QSAR (Quantitative Structure Activity Relationship)
Butanone 78-93-3	EC50	5.091 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
2-aminoethanol 141-43-5	EC50	27,04 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Hydrocarbons, C10-C13, n-	EL50	> 1.000 mg/l	48 h	Daphnia magna	OECD Guideline 202

alkanes, isoalkanes, cyclics, < 2% aromatic -----					(Daphnia sp. Acute Immobilisation Test)

Chronic toxicity (aquatic invertebrates):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances **CAS-No.**	**Value type**	**Value**	**Exposure time**	**Species**	**Method**
Propan-2-ol 67-63-0	NOEC	30 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Ethanol 64-17-5	NOEC	9,6 mg/l	9 d	Daphnia magna	not specified
2-aminoethanol 141-43-5	NOEC	0,85 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatic -----	NOELR	> 10,2 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Methylal 109-87-5	EC10	> 500 mg/l	96 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
1,3-Dioxolane 646-06-0	NOEC	877 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
1,3-Dioxolane 646-06-0	EC50	> 877 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Propan-2-ol 67-63-0	EC50	> 1.000 mg/l	96 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Propan-2-ol 67-63-0	NOEC	1.000 mg/l	96 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Ethanol 64-17-5	EC50	275 mg/l	72 h	Chlorella vulgaris	OECD Guideline 201 (Alga, Growth Inhibition Test)
Ethanol 64-17-5	EC10	11,5 mg/l	72 h	Chlorella vulgaris	OECD Guideline 201 (Alga, Growth Inhibition Test)
Butane, n- (< 0.1 % butadiene) 106-97-8	EC50	7,71 mg/l	96 h		QSAR (Quantitative Structure Activity Relationship)
Butanone 78-93-3	EC50	1.240 mg/l	96 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Butanone 78-93-3	EC10	1.010 mg/l	96 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
2-aminoethanol 141-43-5	EC50	2,8 mg/l	72 h	Pseudokirchneriella subcapitata (reported as Raphidocelis subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
2-aminoethanol 141-43-5	EC10	0,7 mg/l	72 h	Pseudokirchneriella subcapitata (reported as Raphidocelis subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatic -----	EL50	> 1.000 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatic -----	NOELR	1.000 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)

Toxicity (microorganisms):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Methylal 109-87-5	EC10	3.000 mg/l	17 h		DIN 38412, part 8 (Pseudomonas Zellvermehrungshemm-Test)
1,3-Dioxolane 646-06-0	EC50	> 100 mg/l	3 h	activated sludge of a predominantly domestic sewage	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Propan-2-ol 67-63-0	EC50	> 1.000 mg/l	3 h	activated sludge	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Ethanol 64-17-5	IC50	> 1.000 mg/l	3 h	activated sludge	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Butanone 78-93-3	EC50	1.150 mg/l	16 h	Pseudomonas putida	DIN 38412, part 8 (Pseudomonas Zellvermehrungshemm-Test)
2-aminoethanol	EC10	> 1.000 mg/l	3 h	activated sludge, domestic	OECD Guideline 209

141-43-5					(Activated Sludge, Respiration Inhibition Test)

12.2. Persistence and degradability

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
Methylal 109-87-5	not readily biodegradable.	aerobic	> 0 - < 60 %	28 d	OECD 301 A - F
Propane 74-98-6	readily biodegradable	aerobic	> 60 %	28 d	OECD 301 A - F
1,3-Dioxolane 646-06-0	not readily biodegradable.	aerobic	3,7 %	35 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Propan-2-ol 67-63-0	readily biodegradable	aerobic	70 - 84 %	30 d	EU Method C.4-E (Determination of the "Ready" BiodegradabilityClosed Bottle Test)
Ethanol 64-17-5	readily biodegradable	aerobic	80 - 85 %	30 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Butane, n- (< 0.1 % butadiene) 106-97-8	readily biodegradable	aerobic	> 60 %	28 d	OECD 301 A - F
Butanone 78-93-3	readily biodegradable	aerobic	98 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
2-aminoethanol 141-43-5	readily biodegradable	aerobic	> 80 %	19 d	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatic -----	readily biodegradable	aerobic	80 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	LogPow	Temperature	Method
1,3-Dioxolane 646-06-0	-0,35	20 °C	QSAR (Quantitative Structure Activity Relationship)
Propan-2-ol 67-63-0	0,05		OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
Ethanol 64-17-5	-0,35	24 °C	not specified
Butane, n- (< 0.1 % butadiene) 106-97-8	2,31	20 °C	other (measured)
Butanone 78-93-3	0,3	40 °C	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
2-aminoethanol 141-43-5	-1,91	25 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)

12.5. Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or vPvB.

12.6. Endocrine disrupting properties

not applicable

12.7. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:
Do not empty into drains / surface water / ground water.
Dispose of in accordance with local and national regulations.

Disposal of uncleaned packages:
After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Waste code

14 06 03 Other solvents and solvent mixtures
The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

SECTION 14: Transport information

14.1. UN number or ID number

ADR	1950
RID	1950
ADN	1950
IMDG	1950
IATA	1950

14.2. UN proper shipping name

ADR	AEROSOLS
RID	AEROSOLS
ADN	AEROSOLS
IMDG	AEROSOLS
IATA	Aerosols, flammable

14.3. Transport hazard class(es)

ADR	2.1
RID	2.1
ADN	2.1
IMDG	2.1
IATA	2.1

14.4. Packing group

ADR	
RID	
ADN	
IMDG	
IATA	

14.5. Environmental hazards

ADR	not applicable
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

14.6. Special precautions for user

ADR	not applicable Tunnelcode: (D)
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Ozone Depleting Substance (ODS) (Regulation (EC) No 2024/590):	Not applicable
Prior Informed Consent (PIC) (Regulation (EU) No 649/2012):	Not applicable
Persistent organic pollutants (Regulation (EU) 2019/1021):	Not applicable

VOC content (2010/75/EC)	92,09 %

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H220 Extremely flammable gas.
H225 Highly flammable liquid and vapour.
H280 Contains gas under pressure; may explode if heated.
H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

Abbreviations and acronyms:

ADG(-Code): Australian Dangerous Goods (Code)
ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road
ASTM: American Society for Testing and Materials
ATE: acute toxicity estimate
AS: Australian Standard
AwSV: Ordinance on Installations for the Handling of Substances Hazardous to Water
CAS: Chemical Abstract Service
CLP: Regulation (EC) No 1272/2008
CMR: cancerogenic, mutagenic or reprotoxic
DIN: German Institute for Standardization
ECx: Effective concentration (x% effective level)
ECHA: European Chemicals Agency
EC-Nummer: Substance number in the EU-inventories EINECS/ELINCS
ECTLV: European community threshold limit value
ED:Substance identified as having endocrine disrupting properties
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
EN : European Standard
ENCS: Japanese chemical inventory
EPA: US Environmental Protection Agency
EU: European Union
EU EXPLD1: Substance listed in Annex I, Reg (EC) No. 2019/1148
EU EXPLD2: Substance listed in Annex II, Reg (EC) No. 2019/1148
EWC: European Waste Catalogue
GHS: Globally Harmonised System for Classification and Labelling of Chemicals
GLP: Good Laboratory Practice
HSNO: Hazardous Substances and New Organisms
IARC: International Agency for Research of Cancer
IATA: International Air Transport Association
IBC-Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
IC50: half maximal inhibitory concentration
ICAO: International Civil Aviation Organization
IMDG-Code: International Maritime Code for Dangerous Goods
IMO: International Maritime Organization
ISO: International Standardization Organisation
LC50: Median lethal concentration
LD50: Median lethal dose
MARPOL: International Convention for the Prevention of Marine Pollution from Ships
n.o.s.: not otherwise specified
NO(A)EC: No (adverse) effect concentration
NO(A)EL: No (adverse) effect level
NZS: New Zealand Standard
OECD: Organisation for Economic Co-operation and Development
OEL: Occupational Exposure Limit

OPPT: US EPA Office of Pollution Prevention and Toxics
OPPTS: US EPA Office of Prevention, Pesticides and Toxic Substances
PBT: Persistent, bioaccumulative, toxic
(Q)SAR: (Quantitative) structure–activity relationship
REACH: Regulation (EC) No. 1907/2006
RID: Regulations concerning the International Transport of Dangerous Goods by Rail
SADT: Self Accelerating Decomposition Temperature
SDS: Safety Data Sheet
STOT: Specific Target Organ Toxicity
STOT SE: Specific Target Organ Toxicity - single exposure
STOT RE: Specific Target Organ Toxicity - repeated exposure
SUSMP: Standard for the Uniform Scheduling of Medicines and Poisons
SVHC: Substance of very high concern (REACH Candidate List)
TRGS: German Technical Rules for hazardous substances
UN: United Nations
VOC: Volatile Organic Compound
814.018 VOC Reg CH: Swiss Ordinance 814.018 on the Incentive Tax on Volatile Organic Compounds
vPvB: Very persistent, very bioaccumulative
VwVwS: Administrative Regulation on Substances Hazardous to Waters
WGK: Water hazard class

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel´s Product Safety and Regulatory Affairs Department (SDSinfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,
Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.