Safety Data Sheet according to (EC) No 1907/2006 as amended

SDS No. : 515248
V011.0

TEROSON WX 159 XP

Revision: 15.07.2025
printing date: 10.08.2025
Replaces version from: 01.10.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier
TEROSON WX 159 XP
UFI: Q89H-TX22-U20X-UX1N

1.2. Relevant identified uses of the substance or mixture and uses advised against
Intended use:
Car polish

1.3. Details of the supplier of the safety data sheet
Henkel Ltd
Adhesives
Wood Lane End
HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (1442) 278000

SDSinfo.Adhesive@henkel.com
For Safety Data Sheet updates please visit our website www.mysds.henkel.com or www.henkel-adhesives.com.

1.4. Emergency telephone number
24 Hours Emergency Tel: +44 (0)1442 278497

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Specific target organ toxicity - repeated exposure	Category 2
H373 May cause damage to organs through prolonged or repeated exposure.	
Chronic hazards to the aquatic environment	Category 3
H412 Harmful to aquatic life with long lasting effects.	

2.2. Label elements

Label elements (CLP):

Hazard pictogram:

Contains Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Signal word:	Warning
Hazard statement:	H373 May cause damage to organs through prolonged or repeated exposure. H412 Harmful to aquatic life with long lasting effects.
Supplemental information	EUH066 Repeated exposure may cause skin dryness or cracking. Contains: 1,2-Benzisothiazol-3(2H)-one; 2-methylisothiazol-3(2H)-one May produce an allergic reaction.
Precautionary statement: Prevention	P260 Do not breathe mist/spray. P273 Avoid release to the environment.

2.3. Other hazards

Following substances are present in a concentration ≥ the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in a concentration ≥ the concentration limit for depiction in Section 3 that are assessed to be a PBT, vPvB or ED.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No. EC Number REACH-Reg. No.	Concentration	Classification	Specific Conc. Limits, M-factors and ATEs	Add. Information
Sorbitan monooleate ethoxylate 9005-65-6	5- < 10 %	Aquatic Chronic 3, H412		
Distillates (petroleum), hydrotreated light paraffinic, <3% DMSO 64742-55-8 265-158-7 01-2119487077-29	2,5- <= 10 %	Asp. Tox. 1, H304		
Hydrocarbons, C10, aromatics, <1% naphthalene ----- 01-2119463583-34	2,5- <= 10 %	Asp. Tox. 1, H304 STOT SE 3, H336 Aquatic Chronic 2, H411		
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) 01-2119473977-17	2,5- < 10 %	Asp. Tox. 1, H304 STOT RE 1, H372 Aquatic Chronic 3, H412		
1,2-Benzisothiazol-3(2H)-one 2634-33-5 220-120-9 01-2120761540-60	0,025- < 0,036 % (0,25 %o- < 0,36 %o)	Aquatic Acute 1, H400 Aquatic Chronic 1, H410 Acute Tox. 4, Oral, H302 Skin Irrit. 2, H315 Skin Sens. 1A, H317 Eye Dam. 1, H318 Acute Tox. 2, Inhalation, H330	Skin Sens. 1A; H317; C >= 0,036 % ===== M acute = 1 M chronic = 1 ===== oral:ATE = 450 mg/kg inhalation:ATE = 0,21 mg/l;dust/mist	
bronopol 52-51-7 200-143-0 01-2119980938-15	0,01- < 0,025 % (0,1 %o- < 0,25 %o)	Acute Tox. 3, Inhalation, H331 Acute Tox. 4, Dermal, H312 Acute Tox. 3, Oral, H301 STOT SE 3, H335 Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Acute 1, H400 Aquatic Chronic 2, H411	M acute = 10 ===== inhalation:ATE = 0,5881 mg/l;dust/mist	
2-methylisothiazol-3(2H)-one 2682-20-4 220-239-6 01-2120764690-50	0- < 0,0015 % < 15 ppm)	Acute Tox. 2, Inhalation, H330 Skin Sens. 1A, H317 Aquatic Chronic 1, H410 Skin Corr. 1B, H314 Aquatic Acute 1, H400 Eye Dam. 1, H318 Acute Tox. 3, Dermal, H311 Acute Tox. 3, Oral, H301	Skin Sens. 1A; H317; C >= 0,0015 % ===== M acute = 10 M chronic = 1	

If no ATE values are displayed, please refer to LD/LC50 values in Section 11.
For full text of the H - statements and other abbreviations see section 16 "Other information".

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:
Move to fresh air, consult doctor if complaint persists.

Skin contact:
Rinse with running water and soap. Apply replenishing cream. Change all contaminated clothing.

Eye contact:
Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:
Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed
No data available.

4.3. Indication of any immediate medical attention and special treatment needed
See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media
Suitable extinguishing media:
All common extinguishing agents are suitable.

Extinguishing media which must not be used for safety reasons:
High pressure waterjet

5.2. Special hazards arising from the substance or mixture
In case of fire toxic gases can be released.

5.3. Advice for firefighters
Wear self-contained breathing apparatus.
Wear protective equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures
Wear protective equipment.
Danger of slipping on spilled product.
Keep unprotected persons away.
Avoid contact with skin and eyes.

6.2. Environmental precautions
Do not empty into drains / surface water / ground water.
Inform authorities in the event of product spillage to water courses or sewage systems.

6.3. Methods and material for containment and cleaning up
Remove with liquid-absorbing material (sand, peat, sawdust).
Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections
See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Hygiene measures:
Wash hands before work breaks and after finishing work.
Do not eat, drink or smoke while working.

7.2. Conditions for safe storage, including any incompatibilities
Ensure good ventilation/extraction.
Store in a dry place.
Store in a cool, well-ventilated place.
Keep container tightly sealed.
Keep away from heat and direct sunlight.
> + 15 °C
< + 25 °C

7.3. Specific end use(s)
Car polish

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for
Great Britain

Ingredient [Regulated substance]	ppm	mg/m³	Value type	Short term exposure limit category / Remarks	Regulatory list
Aluminium oxide 1344-28-1 [ALUMINIUM OXIDES, INHALABLE DUST]		10	Time Weighted Average (TWA):		EH40 WEL
Aluminium oxide 1344-28-1 [ALUMINIUM OXIDES, RESPIRABLE DUST]		4	Time Weighted Average (TWA):		EH40 WEL
Glycerol 56-81-5 [Glycerol, mist]		10	Time Weighted Average (TWA):		EH40 WEL

Occupational Exposure Limits

Valid for
Ireland

Ingredient [Regulated substance]	ppm	mg/m³	Value type	Short term exposure limit category / Remarks	Regulatory list
Aluminium oxide 1344-28-1 [ALUMINIUM OXIDES]		4	Time Weighted Average (TWA):		IR_OEL
Aluminium oxide 1344-28-1 [ALUMINIUM OXIDES]		10	Time Weighted Average (TWA):		IR_OEL
Distillates (petroleum), hydrotreated light paraffinic 64742-55-8 [MINERAL OILS THAT HAVE BEEN USED BEFORE IN INTERNAL COMBUSTION ENGINES TO LUBRICATE AND COOL THE MOVING PARTS WITHIN THE ENGINE]				Included in the regulation but with no data values. See regulation for further details	IR_OEL
Distillates (petroleum), hydrotreated light paraffinic 64742-55-8 [MINERAL OIL PURE, HIGHLY & SEVERELY REFINED]		5	Time Weighted Average (TWA):		IR_OEL
Distillates (petroleum), hydrotreated light paraffinic 64742-55-8 [MINERAL OILS THAT HAVE BEEN USED BEFORE IN INTERNAL COMBUSTION ENGINES TO LUBRICATE AND COOL THE MOVING PARTS WITHIN THE ENGINE]			Skin designation:	Can be absorbed through the skin.	IR_OEL

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
Distillates (petroleum), hydrotreated light paraffinic, <3% DMSO 64742-55-8	oral				9,33 mg/kg		
Solvent naphtha (petroleum), heavy arom. -----	Air						no hazard identified
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	Air						no hazard identified
1,2-Benzisothiazol-3(2H)-one 2634-33-5	aqua (freshwater)		0,00403 mg/l				
1,2-Benzisothiazol-3(2H)-one 2634-33-5	aqua (marine water)		0,000403 mg/l				
1,2-Benzisothiazol-3(2H)-one 2634-33-5	Freshwater - intermittent		0,0011 mg/l				
1,2-Benzisothiazol-3(2H)-one 2634-33-5	sewage treatment plant (STP)		1,03 mg/l				
1,2-Benzisothiazol-3(2H)-one 2634-33-5	sediment (freshwater)				0,0499 mg/kg		
1,2-Benzisothiazol-3(2H)-one 2634-33-5	sediment (marine water)				0,00499 mg/kg		
1,2-Benzisothiazol-3(2H)-one 2634-33-5	Soil				3 mg/kg		
1,2-Benzisothiazol-3(2H)-one 2634-33-5	Marine water - intermittent		0,000110 mg/l				
bronopol 52-51-7	aqua (freshwater)		0,001 mg/l				
bronopol 52-51-7	Freshwater - intermittent		0 mg/l				
bronopol 52-51-7	aqua (marine water)		0,001 mg/l				
bronopol 52-51-7	sewage treatment plant (STP)		0,43 mg/l				
bronopol 52-51-7	sediment (freshwater)				0,021 mg/kg		
bronopol 52-51-7	sediment (marine water)				0,009 mg/kg		
bronopol 52-51-7	Soil				0,21 mg/kg		
2-methylisothiazol-3(2H)-one 2682-20-4	aqua (freshwater)		0,00339 mg/l				
2-methylisothiazol-3(2H)-one 2682-20-4	aqua (marine water)		0,00339 mg/l				
2-methylisothiazol-3(2H)-one 2682-20-4	sewage treatment plant (STP)		0,23 mg/l				
2-methylisothiazol-3(2H)-one 2682-20-4	Soil				0,047 mg/kg		
2-methylisothiazol-3(2H)-one 2682-20-4	Freshwater - intermittent		0,00339 mg/l				
2-methylisothiazol-3(2H)-one 2682-20-4	Marine water - intermittent		0,00339 mg/l				

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Distillates (petroleum), hydrotreated light paraffinic, <3% DMSO 64742-55-8	Workers	inhalation	Long term exposure - local effects		5,58 mg/m3	
Distillates (petroleum), hydrotreated light paraffinic, <3% DMSO 64742-55-8	General population	inhalation	Long term exposure - local effects		1,19 mg/m3	
Solvent naphtha (petroleum), heavy arom. -----	Workers	inhalation	Long term exposure - systemic effects		151 mg/m3	no hazard identified
Solvent naphtha (petroleum), heavy arom. -----	Workers	dermal	Long term exposure - systemic effects		12,5 mg/kg	no hazard identified
Solvent naphtha (petroleum), heavy arom. -----	General population	inhalation	Long term exposure - systemic effects		32 mg/m3	no hazard identified
Solvent naphtha (petroleum), heavy arom. -----	General population	dermal	Long term exposure - systemic effects		7,5 mg/kg	no hazard identified
Solvent naphtha (petroleum), heavy arom. -----	General population	oral	Long term exposure - systemic effects		7,5 mg/kg	no hazard identified
1,2-Benzisothiazol-3(2H)-one 2634-33-5	Workers	inhalation	Long term exposure - systemic effects		6,81 mg/m3	
1,2-Benzisothiazol-3(2H)-one 2634-33-5	Workers	dermal	Long term exposure - systemic effects		0,966 mg/kg	
1,2-Benzisothiazol-3(2H)-one 2634-33-5	General population	inhalation	Long term exposure - systemic effects		1,2 mg/m3	
1,2-Benzisothiazol-3(2H)-one 2634-33-5	General population	dermal	Long term exposure - systemic effects		0,345 mg/kg	
bronopol 52-51-7	Workers	dermal	Long term exposure - systemic effects		2 mg/kg	
bronopol 52-51-7	General population	dermal	Long term exposure - systemic effects		0,7 mg/kg	
bronopol 52-51-7	General population	oral	Long term exposure - systemic effects		0,18 mg/kg	
bronopol 52-51-7	Workers	inhalation	Long term exposure - systemic effects		3,5 mg/m3	
bronopol 52-51-7	General population	inhalation	Long term exposure - systemic effects		0,6 mg/m3	
bronopol 52-51-7	Workers	inhalation	Acute/short term exposure - systemic effects		10,5 mg/m3	
bronopol 52-51-7	Workers	inhalation	Long term exposure - local effects		2,5 mg/m3	
bronopol 52-51-7	Workers	inhalation	Acute/short term exposure - local effects		2,5 mg/m3	
bronopol 52-51-7	Workers	dermal	Acute/short term exposure - systemic effects		6 mg/kg	
bronopol 52-51-7	Workers	dermal	Long term exposure - local effects		0,008 mg/cm2	
bronopol 52-51-7	Workers	dermal	Acute/short term exposure - local effects		0,008 mg/cm2	
bronopol 52-51-7	General population	dermal	Long term exposure - local		0,004 mg/cm2	

			effects			
bronopol 52-51-7	General population	dermal	Acute/short term exposure - local effects		0,004 mg/cm2	
bronopol 52-51-7	General population	dermal	Acute/short term exposure - systemic effects		2,1 mg/kg	
bronopol 52-51-7	General population	inhalation	Long term exposure - local effects		0,6 mg/m3	
bronopol 52-51-7	General population	inhalation	Acute/short term exposure - systemic effects		1,8 mg/m3	
bronopol 52-51-7	General population	inhalation	Acute/short term exposure - local effects		0,6 mg/m3	
bronopol 52-51-7	General population	oral	Acute/short term exposure - systemic effects		0,5 mg/kg	
2-methylisothiazol-3(2H)-one 2682-20-4	Workers	inhalation	Long term exposure - local effects		0,021 mg/m3	
2-methylisothiazol-3(2H)-one 2682-20-4	Workers	inhalation	Acute/short term exposure - local effects		0,043 mg/m3	
2-methylisothiazol-3(2H)-one 2682-20-4	General population	inhalation	Long term exposure - local effects		0,021 mg/m3	
2-methylisothiazol-3(2H)-one 2682-20-4	General population	oral	Long term exposure - systemic effects		0,027 mg/kg	
2-methylisothiazol-3(2H)-one 2682-20-4	General population	oral	Acute/short term exposure - systemic effects		0,053 mg/kg	
2-methylisothiazol-3(2H)-one 2682-20-4	General population	inhalation	Acute/short term exposure - local effects		0,043 mg/m3	

Biological Exposure Indices:
None

8.2. Exposure controls:

Engineering controls:
Ensure good ventilation/extraction.

Respiratory protection:
In case of aerosol formation, we recommend wearing of appropriate respiratory protection equipment with ABEK P2 filter (EN 14387).
This recommendation should be matched to local conditions.

Hand protection:
Chemical-resistant protective gloves (EN 374).
Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):
nitrile rubber (NBR; >= 0.4 mm thickness)
Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):
nitrile rubber (NBR; >= 0.4 mm thickness)
This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:
Goggles which can be tightly sealed.
Protective eye equipment should conform to EN166.

Skin protection:
Wear protective equipment.
Protective clothing that covers arms and legs.
Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:
Use only personal protection that's CE-labelled according to Directive 89/686/EEC (Europe) or to Regulation No. 819 of 19 August 1994 (Norway), or equivalent.
The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions.
Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Delivery form	liquid
Colour	White
Odor	characteristic
Physical state	liquid
Melting point	Not applicable, Product is a liquid
Solidification temperature	Not applicable, Determination technically not possible
Initial boiling point	Not applicable, Determination technically not possible
Flammability	The product is not flammable.
Explosive limits	Not applicable, The product is not flammable.
Flash point	100 °C (212 °F)
Auto-ignition temperature	Not applicable, The product is not flammable.
Decomposition temperature	Not applicable, Substance/mixture is not self-reactive, no organic peroxide and does not decompose under foreseen conditions of use
pH (20 °C (68 °F); Conc.: 100 % product)	7 - 10 no method / method unknown
Viscosity (kinematic) (40 °C (104 °F);)	7.693 - 11.538 mm2/s ;.no method / method unknown
Viscosity, dynamic (; 40 °C (104 °F))	5.000 - 15.000 mPa.s no method / method unknown
Solubility (qualitative) (20 °C (68 °F); Solvent: Water)	Not miscible or difficult to mix
Partition coefficient: n-octanol/water	Not applicable Mixture
Vapour pressure (20 °C (68 °F))	< 0,1 mbar
Density (20 °C (68 °F))	1,3 g/ml no method / method unknown
Relative vapour density:	Not applicable, Determination technically not possible
Particle characteristics	Not applicable Product is a liquid

9.2. Other information

Other information not applicable for this product

SECTION 10: Stability and reactivity

10.1. Reactivity
None if used for intended purpose.

10.2. Chemical stability
Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions
See section reactivity

10.4. Conditions to avoid
None if used for intended purpose.

10.5. Incompatible materials
None if used properly.

10.6. Hazardous decomposition products
No decomposition if used according to specifications.

SECTION 11: Toxicological information

General toxicological information:
An allergic reaction cannot be excluded after repeated skin contact.

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Sorbitan monooleate ethoxylate 9005-65-6	LD50	> 5.000 mg/kg	rat	not specified
Distillates (petroleum), hydrotreated light paraffinic, <3% DMSO 64742-55-8	LD50	> 5.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
Hydrocarbons, C10, aromatics, <1% naphthalene -----	LD50	3.492 mg/kg	rat	not specified
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	LD50	> 15.000 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
1,2-Benzisothiazol-3(2H)-one 2634-33-5	Acute toxicity estimate (ATE)	450 mg/kg		Expert judgement
bronopol 52-51-7	LD50	193 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
2-methylisothiazol-3(2H)-one 2682-20-4	LD50	120 mg/kg	rat	EPA OPPTS 870.1100 (Acute Oral Toxicity)

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Distillates (petroleum), hydrotreated light paraffinic, <3% DMSO 64742-55-8	LD50	> 5.000 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
Hydrocarbons, C10, aromatics, <1% naphthalene -----	LD50	> 3.160 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	LD50	> 3.400 mg/kg	rat	not specified
1,2-Benzisothiazol-3(2H)-one 2634-33-5	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
bronopol 52-51-7	LD50	1.600 mg/kg	rat	not specified
2-methylisothiazol-3(2H)-one 2682-20-4	LD50	242 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
Sorbitan monooleate ethoxylate 9005-65-6	LC50	> 5,1 mg/l	dust/mist	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)
Distillates (petroleum), hydrotreated light paraffinic, <3% DMSO 64742-55-8	LC50	> 5,53 mg/l	dust/mist	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)
Hydrocarbons, C10, aromatics, <1% naphthalene -----	LC50	> 6,193 mg/l	vapour	4 h	rat	equivalent or similar to OECD Guideline 403 (Acute Inhalation Toxicity)
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	LC50	> 13,1 mg/l	vapour	4 h	rat	equivalent or similar to OECD Guideline 403 (Acute Inhalation Toxicity)
1,2-Benzisothiazol-3(2H)-one 2634-33-5	Acute toxicity estimate (ATE)	0,21 mg/l	dust/mist			Expert judgement
bronopol 52-51-7	LC50	> 0,588 mg/l	dust/mist	4 h	rat	not specified
bronopol 52-51-7	LC100	1,14 mg/l	dust/mist	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)
bronopol 52-51-7	Acute toxicity estimate (ATE)	0,5881 mg/l	dust/mist	4 h		Expert judgement
2-methylisothiazol-3(2H)-one 2682-20-4	LC50	0,11 mg/l	dust/mist	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Sorbitan monooleate ethoxylate 9005-65-6	not irritating	24 h	rabbit	Draize Test
Distillates (petroleum), hydrotreated light paraffinic, <3% DMSO 64742-55-8	not irritating	24 h	rabbit	not specified
Hydrocarbons, C10, aromatics, <1% naphthalene -----	mildly irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
1,2-Benzisothiazol-3(2H)-one 2634-33-5	moderately irritating	4 h	rabbit	EPA OPP 81-5 (Acute Dermal Irritation)
bronopol 52-51-7	irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
2-methylisothiazol-3(2H)-one 2682-20-4	corrosive	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Sorbitan monooleate ethoxylate 9005-65-6	not irritating		rabbit	Draize Test
Distillates (petroleum), hydrotreated light paraffinic, <3% DMSO 64742-55-8	not irritating		rabbit	equivalent or similar to OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Hydrocarbons, C10, aromatics, <1% naphthalene -----	not irritating		rabbit	equivalent or similar to OECD Guideline 405 (Acute Eye Irritation / Corrosion)
1,2-Benzisothiazol-3(2H)-one 2634-33-5	corrosive	3 h	rabbit	EPA OPP 81-4 (Acute Eye Irritation)
bronopol 52-51-7	Category 1 (irreversible effects on the eye)		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Result	Test type	Species	Method
Sorbitan monooleate ethoxylate 9005-65-6	not sensitising	Guinea pig maximisation test	guinea pig	not specified
Distillates (petroleum), hydrotreated light paraffinic, <3% DMSO 64742-55-8	not sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Hydrocarbons, C10, aromatics, <1% naphthalene -----	not sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
1,2-Benzisothiazol-3(2H)-one 2634-33-5	sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
1,2-Benzisothiazol-3(2H)-one 2634-33-5	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
bronopol 52-51-7	not sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
bronopol 52-51-7	not sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
2-methylisothiazol-3(2H)-one 2682-20-4	sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Sorbitan monooleate ethoxylate 9005-65-6	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		Ames Test
1,2-Benzisothiazol-3(2H)-one 2634-33-5	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
1,2-Benzisothiazol-3(2H)-one 2634-33-5	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
1,2-Benzisothiazol-3(2H)-one 2634-33-5	positive without metabolic activation	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
bronopol 52-51-7	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		not specified
bronopol 52-51-7	positive	in vitro mammalian chromosome aberration test	with and without		not specified
bronopol 52-51-7	negative	mammalian cell gene mutation assay	with and without		not specified
2-methylisothiazol-3(2H)-one 2682-20-4	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
2-methylisothiazol-3(2H)-one 2682-20-4	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
2-methylisothiazol-3(2H)-one 2682-20-4	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Sorbitan monooleate ethoxylate 9005-65-6	negative	oral: gavage		mouse	not specified
1,2-Benzisothiazol-3(2H)-one 2634-33-5	negative	oral: gavage		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
1,2-Benzisothiazol-3(2H)-one 2634-33-5	negative	oral: unspecified		rat	OECD Guideline 486 (Unscheduled DNA Synthesis (UDS) Test with Mammalian Liver Cells in vivo)
bronopol 52-51-7	negative	oral: gavage		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
bronopol 52-51-7	negative	oral: gavage		rat	OECD Guideline 486 (Unscheduled DNA Synthesis (UDS) Test with Mammalian Liver Cells in vivo)
2-methylisothiazol-3(2H)-one 2682-20-4	negative	oral: gavage		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
2-methylisothiazol-3(2H)-one 2682-20-4	negative	oral: gavage		rat	OECD Guideline 486 (Unscheduled DNA Synthesis (UDS) Test with Mammalian Liver Cells in vivo)

Carcinogenicity

No data available.

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
Sorbitan monooleate ethoxylate 9005-65-6	NOAEL P 6.666 mg/kg NOAEL F1 6.666 mg/kg NOAEL F2 6.666 mg/kg	three-generation study	oral: feed	rat	not specified
1,2-Benzisothiazol-3(2H)-one 2634-33-5	NOAEL P 112 mg/kg NOAEL F1 56,6 mg/kg NOAEL F2 56,6 mg/kg	Two generation study	oral: feed	rat	EPA OPPTS 870.3800 (Reproduction and Fertility Effects)
bronopol 52-51-7	NOAEL P > 40 mg/kg NOAEL F1 > 40 mg/kg	One generation study	oral: gavage	rat	not specified
2-methylisothiazol-3(2H)-one 2682-20-4	NOAEL P 200 ppm NOAEL F1 200 ppm NOAEL F2 200 ppm	Two generation study	oral: drinking water	rat	OECD Guideline 416 (Two-Generation Reproduction Toxicity Study)

STOT-single exposure:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Assessment	Route of exposure	Target Organs	Remarks
Hydrocarbons, C10, aromatics, <1% naphthalene -----	May cause drowsiness or dizziness.			
bronopol 52-51-7	May cause respiratory irritation.			

STOT-repeated exposure:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
Sorbitan monooleate ethoxylate 9005-65-6	NOAEL > 3.700 mg/kg	oral: feed	28 d daily	rat	not specified
1,2-Benzisothiazol-3(2H)-one 2634-33-5	NOAEL 150 mg/kg	oral: gavage	28 days daily	rat	OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)
1,2-Benzisothiazol-3(2H)-one 2634-33-5	NOAEL 69 mg/kg	oral: feed	90 days daily	rat	EPA OPP 82-1 (90-Day Oral Toxicity)
bronopol 52-51-7	NOAEL 7 mg/kg	oral: drinking water	104 w daily	rat	not specified
2-methylisothiazol-3(2H)-one 2682-20-4	NOAEL 60 mg/kg	oral: gavage	90 d daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

Aspiration hazard:

No Aspiration toxicity classification

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Viscosity (kinematic) Value	Temperature	Method	Remarks
Distillates (petroleum), hydrotreated light paraffinic, <3% DMSO 64742-55-8	10,3 mm2/s	40 °C	DIN EN ISO 3104	
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	1,74 mm2/s	20 °C	ASTM Standard D7042	

11.2 Information on other hazards

not applicable

SECTION 12: Ecological information

General ecological information:
Do not empty into drains, soil or bodies of water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Sorbitan monooleate ethoxylate 9005-65-6	LC50	471 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Distillates (petroleum), hydrotreated light paraffinic, <3% DMSO 64742-55-8	NOEC	> 5.000 mg/l	7 d	Pimephales promelas	not specified
Distillates (petroleum), hydrotreated light paraffinic, <3% DMSO 64742-55-8	LC50	> 5.000 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Hydrocarbons, C10, aromatics, <1% naphthalene -----	LL50	> 2 - 5 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	LL50	> 10 - 30 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
1,2-Benzisothiazol-3(2H)-one 2634-33-5	LC50	2,15 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
1,2-Benzisothiazol-3(2H)-one 2634-33-5	NOEC	0,21 mg/l	30 d	Oncorhynchus mykiss	OECD Guideline 215 (Fish, Juvenile Growth Test)
bronopol 52-51-7	LC50	41 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
bronopol 52-51-7	NOEC	21,5 mg/l	49 d	Oncorhynchus mykiss	OECD Guideline 210 (fish early lite stage toxicity test)
2-methylisothiazol-3(2H)-one 2682-20-4	LC50	4,77 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)

Toxicity (aquatic invertebrates):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Sorbitan monooleate ethoxylate 9005-65-6	EC50	> 1.000 mg/l	48 h	Daphnia magna	not specified
Distillates (petroleum), hydrotreated light paraffinic, <3% DMSO 64742-55-8	EL50	> 10.000 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Hydrocarbons, C10, aromatics, <1% naphthalene -----	EL50	> 3 - 10 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	EL50	> 10 - 22 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
1,2-Benzisothiazol-3(2H)-one 2634-33-5	EC50	2,9 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
bronopol 52-51-7	EC50	1,4 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute

					Immobilisation Test)
2-methylisothiazol-3(2H)-one 2682-20-4	EC50	0,93 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Chronic toxicity (aquatic invertebrates):

The table below presents the data of the classified substances present in the mixture.

Hazardous substances **CAS-No.**	**Value type**	**Value**	**Exposure time**	**Species**	**Method**
Distillates (petroleum), hydrotreated light paraffinic, <3% DMSO 64742-55-8	NOELR	10 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	NOEC	0,372 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
1,2-Benzisothiazol-3(2H)-one 2634-33-5	NOEC	1,2 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
bronopol 52-51-7	NOEC	0,27 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
2-methylisothiazol-3(2H)-one 2682-20-4	NOEC	0,04 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Sorbitan monooleate ethoxylate 9005-65-6	EC50	> 10 - 100 mg/l		Skeletonema costatum	not specified
Distillates (petroleum), hydrotreated light paraffinic, <3% DMSO 64742-55-8	NOELR	100 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Hydrocarbons, C10, aromatics, <1% naphthalene -----	EL50	> 1 - 3 mg/l	72 h	Raphidocelis subcapitata (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Hydrocarbons, C10, aromatics, <1% naphthalene -----	NOELR	1 mg/l	72 h	Raphidocelis subcapitata (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	EL50	4,1 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	NOELR	0,76 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
1,2-Benzisothiazol-3(2H)-one 2634-33-5	EC50	0,1087 mg/l	24 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
1,2-Benzisothiazol-3(2H)-one 2634-33-5	EC10	0,0264 mg/l	24 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
bronopol 52-51-7	EC50	0,026 mg/l	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
bronopol 52-51-7	EC10	0,013 mg/l	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
2-methylisothiazol-3(2H)-one 2682-20-4	NOEC	0,03 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
2-methylisothiazol-3(2H)-one 2682-20-4	EC50	0,22 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)

Toxicity (microorganisms):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Sorbitan monooleate ethoxylate 9005-65-6	EC0	> 100 mg/l		Pseudomonas putida	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
1,2-Benzisothiazol-3(2H)-one 2634-33-5	EC50	23 mg/l	3 h	activated sludge of a predominantly domestic sewage	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
bronopol 52-51-7	EC50	43 mg/l	3 h	activated sludge	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
2-methylisothiazol-3(2H)-one 2682-20-4	EC50	41 mg/l	3 h	activated sludge	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

12.2. Persistence and degradability

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
Sorbitan monooleate ethoxylate 9005-65-6	not inherently biodegradable	aerobic	50 %		OECD Guideline 302 B (Inherent biodegradability: Zahn-Wellens/EMPA Test)
Sorbitan monooleate ethoxylate 9005-65-6	not readily biodegradable.	aerobic	52 %		OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I))
Distillates (petroleum), hydrotreated light paraffinic, <3% DMSO 64742-55-8	not readily biodegradable.	aerobic	31 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Hydrocarbons, C10, aromatics, <1% naphthalene -----	not readily biodegradable.	aerobic	49,56 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	readily biodegradable	aerobic	74,7 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
1,2-Benzisothiazol-3(2H)-one 2634-33-5	not readily biodegradable.	aerobic	42,1 %	28 d	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
bronopol 52-51-7	readily biodegradable	aerobic	> 70 - 80 %	28 d	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
bronopol 52-51-7	not inherently biodegradable	aerobic	50 %	45 d	OECD Guideline 302 B (Inherent biodegradability: Zahn-Wellens/EMPA Test)
2-methylisothiazol-3(2H)-one 2682-20-4	inherently biodegradable	aerobic	97 %	48 h	OECD Guideline 302 B (Inherent biodegradability: Zahn-Wellens/EMPA Test)
2-methylisothiazol-3(2H)-one 2682-20-4	readily biodegradable	aerobic	> 70 %	28 d	OECD Guideline 309 (Aerobic Mineralisation in Surface WaterSimulation Biodegradation Test)

12.3. Bioaccumulative potential

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Bioconcentration factor (BCF)	Exposure time	Temperature	Species	Method
1,2-Benzisothiazol-3(2H)-one 2634-33-5	6,62	56 d		not specified	other guideline:

12.4. Mobility in soil

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	LogPow	Temperature	Method
1,2-Benzisothiazol-3(2H)-one 2634-33-5	0,7	20 °C	EU Method A.8 (Partition Coefficient)
bronopol 52-51-7	0,15	23 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
2-methylisothiazol-3(2H)-one 2682-20-4	-0,5		OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)

12.5. Results of PBT and vPvB assessment

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	PBT / vPvB
Distillates (petroleum), hydrotreated light paraffinic, <3% DMSO 64742-55-8	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Hydrocarbons, C10, aromatics, <1% naphthalene -----	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
1,2-Benzisothiazol-3(2H)-one 2634-33-5	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
bronopol 52-51-7	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
2-methylisothiazol-3(2H)-one 2682-20-4	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

12.6. Endocrine disrupting properties

not applicable

12.7. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:
In consultation with the responsible local authority, must be subjected to special treatment.

Waste code

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.
080409

SECTION 14: Transport information

14.1. UN number or ID number

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.2. UN proper shipping name

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.3. Transport hazard class(es)

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.4. Packing group

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.5. Environmental hazards

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.6. Special precautions for user

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Ozone Depleting Substance (ODS) (Regulation (EC) No 2024/590):	Not applicable
Prior Informed Consent (PIC) (Regulation (EU) No 649/2012):	Not applicable
Persistent organic pollutants (Regulation (EU) 2019/1021):	Not applicable
VOC content (2010/75/EU)	13,5 %

VOC Paints and Varnishes (EU):

Regulatory Basis:	Directive 2004/42/EC
Product (sub)category:	B(e) Special finishes
Phase I (from 1.1.2007):	840 g/l
max. VOC content:	175,5 g/l

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text
of all abbreviations indicated by codes in this safety data sheet are as follows:

H301 Toxic if swallowed.
H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H311 Toxic in contact with skin.
H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H330 Fatal if inhaled.
H331 Toxic if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H372 Causes damage to organs through prolonged or repeated exposure.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

ED:	Substance identified as having endocrine disrupting properties
EU OEL:	Substance with a Union workplace exposure limit
EU EXPLD 1:	Substance listed in Annex I, Reg (EC) No. 2019/1148
EU EXPLD 2	Substance listed in Annex II, Reg (EC) No. 2019/1148
SVHC:	Substance of very high concern (REACH Candidate List)
PBT:	Substance fulfilling persistent, bioaccumulative and toxic criteria
PBT/vPvB:	Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very bioaccumulative criteria
vPvB:	Substance fulfilling very persistent and very bioaccumulative criteria

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel´s Product Safety and Regulatory Affairs Department (SDSinfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,
Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.